Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE 1/4 NWSE 1/4 30 Т 27 S 1WDistance and direction from nearest town or city street address of well if located within city? 204 Autumn Blaze Goddard, Kansas GEORGE, MIKE CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 3732 N. Smyser Ct. CITY, STATE: Wichita, Kansas ZIP CODE Application Number 65 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: ELEVATION: ft. ft. ft. Depth of groundwater Encountered: 35 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/30/14 Pump test data: Well water was ft. after hours of pumping @ apm NW NE ft. after Est. Yield: gpm Well water was hours of pumping @ apm Ξ Bore Hole Diameter 12 to **65** and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering Ìε 5. Public water supply 7. Lawn and garden only SW 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? ( NO s YES submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: C Glued Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 50 ft., Dia. Dia. ft Blank casing diameter in to in. to in. to 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9 ABS 1. Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 1. Continuous slot 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 50 From to ft. From ft ft. to ft. to ft., From From ft. ft. to 24 ft. GRAVEL PACK INTERVALS: to 65 From From ft., ft. From ft. to ft. From ft to ft. **GROUT MATERIALS:** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft., From ft ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? 20 ft. plus Direction from well? LITHOLOGIC LOG From Τo LITHOLOGIC LOG From Τо 3 topsoil 0 50 clay 3 50 medium sand 60 60 65 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and 3

was completed on (mo/day/year) 10/30/2014 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/03/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp