WATE	R WEI	LL RECORD	Form WWC-5	Division of Water Resources App. No.	
		OF WATER WELL:	Fraction	Section Number Township No. Range Number	
	nty: Sec		¼ ¼ NW ¼ NE		
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) inform					
from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees)	
Ì	ĺ	4302 W. Has	20ther	Longitude: (in decimal degrees)	
Well#2			(m) #)	Elevation:	
2 WATER WELL OWNER: Vision Homes				Datum: WGS 84, NAD 83, NAD 27	
RR#, Street Address, Box #: Box 224				Collection Method: GPS unit (Make/Model:)	
City, State, ZIP Code : Colwich, KS 67030				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
	,,	CONVICTI	, K3 07030	Est. Accuracy:	
3 LOCATE WELL					
	H AN "X	"IN 4 DEPTH OF	COMPLETED WELL .1.19	ft.	
SEC	SECTION BOX: N Depth(s) Groundwater Encountered (1).45 ft. (2)				
	WELL'S STATIC WATER LEVEL				
	Pump test data: Well water was				
	W NE - NW - NE - EST. YIELD. 15gpm. Well water was				
W					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
	☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well				
S If yes, mo/day/yr sample was submitted					
water well disinfected?					
water were districted: Eg. 165 🗀 140					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter .5 in. to .110 ft., Diameter in. to ft., Diameter in. to ft.					
				lbs./ft., Wall thickness or gauge No	
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From40 ft. to110 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 110 ft., From ft. to ft.					
From					
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other					
Grout Intervals: From .3					
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)					
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well					
Direc	ction from	n well East		nce from well13.'	
FROM	TO	LITHOLOG	IC LOG FRON	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0	3	Topsoil			
3	25	Clay			
25	35	Sand			
35	110	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) .02/20/20.15 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 238 This Water Well Record was completed on (mo/day/year) .02/23/2015					
under the business name of . Premier Pump & Well Service, Inc					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					