


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>SE 1/4 NW 1/4 NW 1/4</u>	Section Number <u>13</u>	Township Number <u>T 27 S</u>	Range Number <u>R 1 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3318 W. 9th N.</u>					
2 WATER WELL OWNER: <u>Disseeby</u> RR#, St. Address, Box # : <u>4614 W. 11th</u> City, State, ZIP Code : <u>Wichita, KS 67112</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>36</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>12</u> ft. 2. <u>36</u> ft. 3. <u>4-20-98</u> ft. WELL'S STATIC WATER LEVEL <u>12</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>25</u> gpm. Well water was <u>36</u> ft. after <u>7</u> hours pumping <u>36</u> gpm Est. Yield <u>25</u> gpm. Well water was <u>36</u> ft. after <u>7</u> hours pumping <u>36</u> gpm Bore Hole Diameter <u>7</u> in. to <u>36</u> ft. and <u>36</u> in. to <u>36</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> Blank casing diameter <u>5</u> in. to <u>27</u> ft. Dia <u>2.40</u> in. to <u>36</u> ft. Dia <u>160 PSI</u> Casing height above land surface <u>12</u> in. weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>160 PSI</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>12</u> ft. to <u>36</u> ft. From <u>12</u> ft. to <u>36</u> ft. GRAVEL PACK INTERVALS: From <u>12</u> ft. to <u>36</u> ft. From <u>12</u> ft. to <u>36</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>12</u> ft. to <u>36</u> ft. From <u>12</u> ft. to <u>36</u> ft. From <u>12</u> ft. to <u>36</u> ft. From <u>12</u> ft. to <u>36</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>northeast</u> How many feet? <u>12</u>					
FROM		TO		LITHOLOGIC LOG	
0 2		11		topsoil	
2 11		18		clay	
11 18		19		fine sand	
18 19		36		clay	
19 36				gravel	
FROM		TO		PLUGGING INTERVALS	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-20-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>5-4-98</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Nichole Spiggs</u>					