

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW 1/4 SW 1/4 SW 1/4	10	T 27 S	R 1 W E/W
Distance and direction from nearest town or city street address of well if located within city? 13th & Ridge Rd., NE corner Wichita, Ks.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 56 ft. ELEVATION:			
N 1 Mile W E S X		Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 9-2-83			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 30 in. to ft., and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well		2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Observation well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped X			
1 Steel 3 RMP (SR) 6 <u>Asbestos-Cement</u> 9 Other (specify below) Welded		2 PVC 4 ABS 7 <u>Fiberglass</u> <u>Transite</u> Threaded			
Blank casing diameter 16 in. to 30 in. Dia. in. to ft., Dia. in. to ft.		Casing height above land surface 12 in., weight 37 lbs./ft. Wall thickness or gauge No. 3/4			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 <u>Asbestos-cement - Transite</u>			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 30 ft. to 56 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 10 ft. to 56 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		4 Other			
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft.		10 Livestock pens 14 Abandoned water well			
What is the nearest source of possible contamination:		11 Fuel storage 15 Oil well/Gas well			
1 Septic tank 4 Lateral lines 7 Pit privy 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None. Apparent.			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	6	Fine Sand			
6	14	Fine-Coarse Sand			
14	20	Clay			
20	25	Fine Sand			
25	34	Fine-Coarse Sand			
34	46	Medium-Coarse Sand & Gravel			
46	56	Clay with some Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-2-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 12-30-83 under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>					
INSTRUCTIONS: Use typewriter or ball point pen, <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E/W

SEC.

10

SW 1/4

SW 1/4

SW 1/4

SW 1/4