WATER WELL R		m WWC-5		sion of Water			
Original Record		nange in Well Use		rces App. No.		Well ID	
1 LOCATION OF W		Fraction	1	ion Number	Township Numb	l (**)	
County: Sed	gwick	5e 1/4 se 1/4 AW1/4			<u>S</u> (S	R DE KOW	
2 WELL OWNER: La	•	First:				(if unknown, distance and	
Address: 1)	in Lesli	e	direction from ne	tion from nearest town or intersection): If at owner's address, check here:			
Addmin .						1 vc	
City:	State:	ZIP:	4020	, W. 3	10 h Mich	ita KS	
3 'LOCATE WELL	4 DEPTH OF C	OMPLETED WELL: .	50 ft	5 Latitude	. .	(decimal decrees)	
Depth(s) Groundwater Encountered: 1)							
SECTION BOX: 2)			Dry Well	Datum: WGS 84 NAD 83 NAD 27			
WELL'S STATIC WATER LEVEL:				Source for Latitude/Longitude:			
below land surface, measured on (mo-day-yr above land surface, measured on (mo-day-yr Pump test data: Well water was			yr)			·)	
				(WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map			
E after hours pumpinggp				Onli	ne Mapper:		
Well water was ft. after hours pumping gpm				<u> </u>			
	Estimated Yield:		gpin	6 Elevatio	n:ft.	. Ground Level TOC	
S		er: in. to	ft. and			GPS Topographic Map	
mile		in. to			☐ Other		
7 WELL WATER TO				· L			
1. Domestic:		Water Supply: well ID	•••••	10. □ Oil F	ield Water Supply: le	ease	
☐ Household		tering: how many wells?		11. Test Hole: well ID			
🔀 Lawn & Garden		er Recharge: well ID		☐ Case	d 🗌 Uncased 🔲 🤆	Geotechnical	
☐ Livestock		toring: well ID			mal: how many bores		
2. Irrigation		nental Remediation: well II			ed Loop Horizont		
3. Feedlot	☐ Air Sp		Extraction			scharge 🔲 Inj. of Water	
4. Industrial		very Injection					
		ubmitted to KDHE?	Yes 🔀 No	If yes, date sa	ample was submitte	xd:	
Water well disinfected?		* '					
8 TYPE OF CASING USED: Steel PVC Other							
Casing diameter	in. to	ft., Diameter	in. to	ft., Diamete	er in. to	ft.	
Casing height above land	surface	in. Weight	in. to lbs./ft.	ft., Diamete Wall thickne	erin. to ss or gauge No	ft.	
Casing height above land TYPE OF SCREEN OF	surface	in. Weight MATERIAL:	in. to lbs./ft.	Wall thickne	ss or gauge No	<i>a.</i> Q	
Casing height above land TYPE OF SCREEN OF Steel Stair	surface	in. Weight MATERIAL: Fiberglass ☑ PVC	lbs./ft.	Wall thickne ☐ Other	ss or gauge No	a0	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv	surface	in. Weight MATERIAL: Fiberglass ☑ PVC Concrete tile ☐ None v	in. to	Wall thickne ☐ Other	ss or gauge No	<i>a.</i> Q	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR	surface	in. Weight	lbs./ft.	Wall thickne ☐ Other)	ss or gauge No	e.C	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	in. Weight	lbs./ft. used (open hole) orch Cut	Wall thickne ☐ Other) rilled Holes [ss or gauge No	<i>a.</i> Q	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter	surface	in. Weight	lbs./ft. used (open hole) orch Cut	Wall thickne ☐ Other) rilled Holes ☐ one (Open Hole	ss or gauge No	e.C	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI	surface	in. Weight	used (open hole) orch Cut Draw Cut No.	Wall thickne Other Other Control of the control	Ss or gauge No	e.C	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE	surface	in. Weight	used (open hole) orch Cut Dr ow Cut No ft., From ft., From	Wall thickne Other Other One (Open Hole ft. to ft. to	Ss or gauge No	ft. to ft.	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE 9 GROUT MATERIA	surface	in. Weight	ised (open hole) orch Cut Draw Cut No	Wall thickne Other Other Other illed Holes one (Open Hole ft. to ther	Ss or gauge No	ft. to ft ft.	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible	Surface	min. Weight MATERIAL: Fiberglass	orch Cut Draw Cut No ft., From ft., From ft., to	Wall thickne Other Other Other One (Open Hole ft. to ther ft., From	Ss or gauge No	### ### ##############################	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank	Surface	in. Weight	ised (open hole) orch Cut Drive Cut No	Wall thickne Other Other Other One (Open Hole ft. to ther ther Livestock Pens	Ss or gauge No	### ### ##############################	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines	Surface	in. Weight	ised (open hole) orch Cut Driew Cut No	Wall thickne Other Other Other Other Other Other It to	Specify	ft. to ft ft. ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line	surface	in. Weight	ised (open hole) orch Cut Dr. w Cut No ft., From ft., From entonite Or ft. to	Wall thickne Other Other Other One (Open Hole ft. to ther ther Livestock Pens	Specify	### ### ##############################	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line	surface	mATERIAL: Fiberglass PVC Concrete tile None us S ARE: Gauze Wrapped Serom Sero	ised (open hole) orch Cut Dr. ow Cut No ft., From ft., From entonite Or ft. to	Wall thickne Other Ot	Other (Specify)	ft. to ft ft ft ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well?	Surface	in. Weight MATERIAL: Fiberglass Concrete tile S ARE: Gauze Wrapped Sare From 16. to Cement grout Lines H. From Distance from weight Materials PVC PVC PVC PVC PVC PVC PVC Sare PT T Sare PT B B Cement grout Sewage La B Cement Grout Sewage La Cepit Feedyard	ised (open hole) orch Cut Driw Cut No cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft ft. ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	Surface	mATERIAL: Fiberglass PVC Concrete tile None us S ARE: Gauze Wrapped Serom Sero	ised (open hole) orch Cut Dr. ow Cut No ft., From ft., From entonite Or ft. to	Wall thickne Other Ot	Ss or gauge No	ft. to ft ft ft ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well?	Surface R PERFORATION I calculate the street in the stree	in. Weight	ised (open hole) orch Cut Driw Cut No cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft ft. ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	Surface R PERFORATION I calculate the street in the stree	material:	ised (open hole) orch Cut Driw Cut No cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft ft. ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	Surface R PERFORATION In the service of the servic	in. Weight	ised (open hole) orch Cut Driw Cut No cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PACE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 10	Surface R PERFORATION In the service of the servic	mATERIAL: Fiberglass PVC Concrete tile None us SARE: Gauze Wrapped Sare From 16 ft. to 50 Cement grout Beautiff Beautiff Beautiff Beautiff Sewage Late Pit Freedyard Distance from wellogic LOG	ised (open hole) orch Cut Driw Cut No cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	Surface R PERFORATION In the service of the servic	material:	ised (open hole) orch Cut Driw Cut No cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PACE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 10	Surface R PERFORATION In the service of the servic	mATERIAL: Fiberglass PVC Concrete tile None us SARE: Gauze Wrapped Sare From 16 ft. to 50 Cement grout Beautiff Beautiff Beautiff Beautiff Sewage Late Pit Freedyard Distance from wellogic LOG	ised (open hole) orch Cut Driw Cut No cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PACE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 10	Surface R PERFORATION In the service of the servic	mATERIAL: Fiberglass PVC Concrete tile None us SARE: Gauze Wrapped Sare From 16 ft. to 50 Cement grout Beautiff Beautiff Beautiff Beautiff Sewage Late Pit Freedyard Distance from wellogic LOG	sed (open hole) orch Cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 15 40 40 41 41 50	Surface	material:	ised (open hole) orch Cut	Wall thickne Other Ot	Sor gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 15 40 40 41 41 50	Surface	material:	ised (open hole) orch Cut	Wall thickne Other Ot	Sor gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 15 40 40 41 41 50	Surface	material:	ised (open hole) orch Cut	Wall thickne Other Ot	Sor gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 15 15 15 15 15 1	Surface	MATERIAL: Fiberglass PVC Concrete tile None us S ARE: Gauze Wrapped Sare From S. ft. to S. S. ft. ft. ft. ft. ft. ft. ft. ft. ft. ft	Ibs./ft. Issed (open hole) Orch Cut	Wall thickne Other Ot	Ss or gauge No	ft. to	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 10 40 41 50 11 CONTRACTOR'S under my jurisdiction a Kansas Water Well Counder the business nam	SUPERFORATION IN THE SANDOWN IN THE	min. Weight MATERIAL: Fiberglass Concrete tile S ARE: Gauze Wrapped Sare From 1/8 ft. to 50 Cement grout Lines Fit, From Distance from wologic Log Clay Grave Clay C	Ibs./ft. seed (open hole) orch Cut	Wall thickne Other Ot	Ss or gauge No	ft. to ft. ft. to ft. ft. to ft. cide Storage oned Water Well ell/Gas Well r PLUGGING INTERVALS onstructed, or plugged by knowledge and belief. ear) 2: 25.15	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 15 15 16 16 17 17 18 19 10 10 10 10 10 10 10 10 10 10 10 10 10	SURFACE STEEL STEE	MATERIAL: Fiberglass PVC Concrete tile None us S ARE: Gauze Wrapped Sare From S. ft. to S. S. ft. ft. ft. ft. ft. ft. ft. ft. ft. ft	Ibs./ft. Issed (open hole) Orch Cut	Wall thickne Other Ot	Ss or gauge No	ft. to	