						10 E 16	04.00 40.	10		
1 LOCATION OF WATE	R WELL:	WATER WE	ELL RECC	JRD F	orm WW	ON NUMBER	SA 82a-121 TOWNSHII		RANGE N	UMBER
L Sedgwick		NW 1/4	SW 1/4	sw	1/4	21	Т 2	7 s	R 1V	V E/W
Distance and direction fro	m nearest town or city st			city?						
141 S. Robin 2 WATER WELL O	OWNER: EPPE	<u>Wichita, Ka</u> RSON, Jim	nsas	***************************************		+ W- 444			A CONTRACTOR OF THE PARTY OF TH	
RR#,ST. ADDRESS		Robin						Board of Agric	ulture, Division of V	Vater Resource
The second contract of	····	ta, Kansas	movii de Santal de S			P CODE:		Application Numb	oer:	
3 LOCATE WELL'S LOW	CTION BOX:	EPTH OF COMPL					ELEVATION:			
N N		h of groundwater ₋ L'S STATIC WA ⁿ		28	ft.	W I WILW	DEACE MEASI	ft. JRED ON mo/da	av/vr 4/21	ft. 2/15
, , , , , , , , , , , , , , , , , , ,	NE		np test data:	Well water		W LAND 30	ft. after		of pumping @	gpm
	1	Est. Yield:	gpm	Well wat	er was		ft. after		of pumping @	gpm
M Mile	'	re Hole Diameter	12	in.	to 4	.5 ft.	and	in.	to	ft.
		LL WATER TO BE Domestic 3. I	E USED AS: Feedlot 5	5. Public wat	er supply	< 7. Lawn a	nd garden only	⊳ ^{9. Dewaterin}	9	ction well pecify below)
		-	ndustrial 6	6. Oil field wa	ater supply			10. Monitoring	g well	. , ,
S		is a chemical/bacteri mitted	ological sample	submitted to D	epartment?	YES Was V	NO Vater Well Disin		hat mo/day/yr	was sample NO
5 TYPE OF CAS		5. Wrought I	ron 7	. Fiberglass	9. Ot	ther (Specify		SING JOINTS: C	Glued	Threaded
1. Steel	3. RPM (SR)				SD1	R-26	,		Welded	Clamped
2. PVC	> 4. ABS er 5 ir	6. Asbestos	-Cement o 20 ft.,	. Concrete til Dia.	в		ft	Dia. ii	n. to	ft.
Blank casing diamet		10	',		in. 2.35 It	to	ft.,			
Casing height above	OR PERFORATION	,		Weight:	2.33 II	os. / ft.	vvaliti	ickness or gaug	e No214	•
1	3. Stainless Steel	5. Fiberglass	7.	PVC	9. A	BS	11. O	her (specify)		
2. Brass	4. Galvanized	6. Concrete Ti	le 8.	RMP (SR)	10. A	sbestos-Cer	nent 12. No	one used (open h	nole)	
	DRATION OPENING			4	-7 -7- -		0 D.:!!	lad balaa	11 None (onen hele)
1. Continuous slot 3. Mill slot 5. Gauzed wrapped						7. Torch cut 9. Drilled holes 8. Saw cut 10. Other (specify)			11. None (open hole)	
2. Louvered shutte	, ,		Vire wrapped					er (specify)		
SCREEN - PERFORA	ATION INTERVAL	From	20 ft.	to	45	ft.,	From	ft.	to	ft.
GRAVEL BA	ACK INTERVALS:	From	ft. 20 ft.	to to	45	ft., ft.,	From From	ft.	to	ft.
GRAVELF	ON INTERVALS.	From From	£0 ft.	to		ft.,	From	ft. ft.	to	ft.
6 GROUT MATER	IALS: 1. Neat c		2. Cement			Bentonite	1 10111		onite hole pl	ft.
Grout Intervals:	From 0	ft. to	20 ft.,	From	ft.	to	ft.,	From	ft. to	0
What is the nearest source of possible contamination:					. Livestock pens		•	icide storage	15. Oil well /	
1. Septic tank 4. Lateral lines 7. Fit privy 10. Elves 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel						•	14. Abandon water well 16. Other (specify belo			
3. Watertight sew		501	Feed yard		2. Fertilize	_	11.7100110			
Direction from well?	West		-				How m	any feet? 20 f		
From To		<u>ITHOLOGIC</u>	LOG		From	То		LITHOLO	GIC LOG	
$\begin{array}{c c} 0 & 3 \\ \hline 3 & 12 \end{array}$	topsoil clay									
12 20	clay and fine s	and								***
20 45	medium sand	**************************************							***************************************	·····
	 							-		
		**************************************		N						
					 	 				
			Minimum Minimum Market							
171			/					ا المعامدة	بالمطاسيين يتميين سماسمين	otion and

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 4/22/2015 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 4/24/2015 Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp