WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: RANGE NUMBER FRACTION SECTION NUMBER TOWNSHIP NUMBER Sedgwick SW NE NW28 27 R 1W E/W 1/4 1/4 Т S Distance and direction from nearest town or city street address of well if located within city? 437 S. Flovd Wichita, Kansas WATER WELL OWNER: BAKER, Annette Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 437 S. Floyd CITY, STATE Wichita, Kansas Application Number: ZIP CODE 45 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NE Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ⋚ 12 Bore Hole Diameter to 45 and in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? C NO (YES) NO submitted Was Water Well Disinfected? TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 20 Dia. ft., Dia ft. in. ft., in. in. to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 9. ABS 1 Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 6. Wire wrapped 2. Louvered shutter 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 20 ft 45 ft., From tο From ft. ft. ft. From to ft., From ft. to ft. **GRAVEL PACK INTERVALS:** 20 ft. to 45 ft From From fŧ to ft. ft From to ft.. From ft. ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2 Cement Grout 3. Bentonite O 20 Grout Intervals: From ft ft., From ft. to ft. ft., From What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit How many feet? 20 ft. plus Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG Τо From To Û topsoil 3 15 clay 15 fine sand medium sand

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 4/23/2015 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

4/27/2015

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp