WATER	WEL	L RECORD	Form WV	VC-5			r Resources App. N		
1 LOCATION OF WATER WELL:		Fraction	014/ 1/	Section Number Town 9 T			Range Number R 1 □E ☑W		
Count	y: Sedo	wick	1/4 SE 1/4 NW	Clobal	_				
Street	/Rural A	ddress of Well Location;	owner's address, check	Latitud	Global Positioning System (GPS) information: Latitude:				
from nearest town or intersection: If at owner's address, check here .						Longitude: (in decimal degrees)			
						Elevation:			
2 WATER WELL OWNER: Jeanette Robertson						Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: 1617 N. Robin Circle					GPS unit (Make/Model:)				
City, State, ZIP Code : Wichita, KS 67212					Digital Map/Photo, Topographic Map, Land Survey				
Est. Accuracy: <3 m, 3-5 m, 5-13 m, >15 h									
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 60									
SECTION POV. Depth(s) Groundwater Encountered (1) 30 ft. (2) ft. (3) ft.									
N WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr									
	\neg	Pump	test data: Well water &gpm. Well water	was	tt.	after	hours pur	npinggpiii	
NW	V N	01 1	neter 1.0in. to .6	was	and	in	. to	.ft.	
w		WELL WATER	TO BE USED AS:	Public wat	er supply	/ ∐ G∈	eothermal \square	injection well	
1 2	/ X s	Domestic .	☐ Feedlet ☐ (Til field wat	er sunnly	· □ D∢	ewatering	Other (Specify below)	
\$w	3	l III Impation	☐ Industrial ☑ I	Domestic-lav	vn & gar	den M	onitoring well	***************************************	
Was a chemical/bacteriological sample submitted to Department? Yes No									
s If yes, mo/day/yr sample was submitted Water well disinfected? Yes No									
5 TYPE OF CASING USED: Steel PVC Other									
Grains dismeter 5 in to 60 ft Diameter in to									
Casing height above land surface 12 in., Weight 2.9 lbs./ft., Wall thickness or gauge No									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)									
SCREEN OR DERECRATION OPENINGS ARE:									
Continuous slot									
COPE	Louvered N. DEDE	Shutter Key punched CORATED INTERVALS:	From 40	i saw cut i to60		. ft., From	ft.	. to ft.	
	GRAV.	EL PACK INTERVALS:	From. 20	ft. to <u>60</u>		. ft., From .	ft	to tt.	
GRAVEL PACK INTERVALS: From 20 ft. to 60 ft., From ft. to ft. From tt. to ft. From ft. to ft. From ft. to ft.									
6 GRO	UT MA	From 3 ft f	ent Cement grout	E Delim	ft. to	ft.	. From	ft. toft.	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 3 ft. to 20 ft., From ft. to ft.									
	Septic ta	nk 🔲 Lateral li	ines 🔲 Pit privy	Livestock	F	Insecticid	-	ther (specify below)	
	Sewer li	nes		☐ Fuel storag		☐ Abandone ☐ Oil well/g			
Direc	tion from	m well South		Distance	from we	1140'	• • • • • • • • • • • • • • • • • • • •		
FROM		LITHOLO	GIC LOG	FROM	TO	LITHO. L	OG (cont.) or PL	UGGING INTERVALS	
0	3	Topsoil							
3	35	Clav							
35	60	Medium Sand		 					
	 		<u> </u>						
	 								
							<u> </u>		
	ļ								
- 605		ODIC OD LANDOWATE	DIS CEDTIFICATIO	N. This was	er well v	vas 🔽 cons	tructed. Trecons	tructed, or Dlugged	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 2 constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 05/11/2015 and this record is true to the best of my knowledge and belief.									
This Water Well Record Was committee in 1100/02/1/1975 This Water Well Record Was committee in 1110/02/1975 This Water W									
under the business name of Premier Pump & Well Service, Inc. by (signature)									
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$3.00 for each constituted with Validation									
http://www.kdheks.gov/waterwell/index.html									