	WATER WELL	RECORD F	orm WV	/C-5 K	SA 82a-12	12			
1 LOCATION OF WATER WELL:	FRACTION	E GTT		ION NUMBER	1	P NUMBER	RANGE N		
Sedgwick	SE 1/4 N		1/4	9	т 2	7 s	R 1V	V E/W	
Distance and direction from nearest town or city		•							
8129 W. Aberdeen	Wichita, Kansa	ıs							
	DT, Robert Goff Rd.					Board of Agric	culture, Division of V	/ater Resource	
·	ey Center, Kansas	1	711	P CODE:		Application Num	thos:		
	DEPTH OF COMPLETE			CODE.	ELEVATION:	Application Num	ibei.		
₩ITH AN "X" IN SECTION BOX:					ELEVATION.				
	oth of groundwater Enco		ft.			ft.	. 4/40	ft.	
	ELL'S STATIC WATER			W LAND SU	JRFACE MEASU		, ,		
	Pump te: Est. Yield:				ft. after ft. after		of pumping @	gpn	
₩ E B	ore Hole Diameter	pm Well wa 12 in.	to 7	0 ft.		in.	of pumping @ to	gpm ft.	
1 1 1	ELL WATER TO BE US		10 /	11.	anu		44 1.1.	tion well	
	Domestic 3. Feed		ter supply	7. Lawn a	and garden only	⊳ ^{9. Dewaterir}	12. Other (Si		
	. Irrigation 4. Indus	strial 6. Oil field w	ater supply	8. Air con	ditioning	10. Monitorin		,	
· ·	/as a chemical/bacteriologic	al sample submitted to [Department?	YES	NO		vhat mo/day/yr v	•	
	bmitted			Was V	Vater Well Disin	fected? (YES I	10	
TYPE OF CASING USED: 1. Steel 3. RPM (SF	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CAS	SING JOINTS: (Glued	Threaded	
2. PVC 4. ABS	6. Asbestos-Cerr	ent 8. Concrete ti	le SDI	R-26			Welded	Clamped	
_	in. to 45	ft., Dia.		4	4	Dia :			
	10	•	in.	to	·		n. to	ft.	
Casing height above land surface:	12 in.,	Weight:	2.35 lb	s. / ft.	Wall th	ickness or gaug	e No214		
TYPE OF SCREEN OR PERFORATION 1 Steel 3. Stainless Steel	I MATERIAL: 5. Fiberglass	7. PVC	9. AI	20	11 Ot	her (specify)			
Steel 3. Stainless Steel Ress 4. Galvanized	6. Concrete Tile	8. RMP (SR)		sbestos-Cen		one used (open l	holo)		
		U. TRIVIE (STR)	10. A	suesius-cei	nent 12. No	me usea (open)	noie)		
SCREEN OR PERFORATION OPENING	-			_					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped				7. Torch cut 9. Drille			ed holes 11. None (open hole)		
2. Louvered shutter 4. Key pu	unched 6. Wire v	vrapped	8. Sa	w cut	10. Oth	er (specify)			
SCREEN - PERFORATION INTERVAL	From 4	5 ft. to	65	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 2	4 ft. to	65	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From				
6 GROUT MATERIALS: 1 Nest						ft.	to	ft.	
Contribute role 5. A. A. A. A. C. Committee of the contribute of t						•			
Grout Intervals: From 4 What is the nearest source of possible co		ft., From	ft.	to	ft.,	From	ft. to	ft.	
1. Septic tank 4. Lateral	7 Dit -	rivy 1	0. Livestoci	k pens	13. Insecti	icide storage	15. Oil well/G	as well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (spec						ecify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? South					How ma	any feet? 60 f	t. plus		
From To	LITHOLOGIC LC)G	From	То		LITHOLO	GIC LOG		
0 3 topsoil									
3 20 clay									
20 35 fine sand									
35 65 medium sand									
7 0					-				
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 4/12/16 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/15/16									
under the business name of Harp Well and Pump Service by (signature)									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									