		WATER W	ELL RE	CORD	Form	wwc	C-5 K	SA 82a-	1212					
111	LOCATION OF WATER WELL: FF					SECTION NUMBER			TOWNSHIP NUMBER			RANGE NUMBER		
Sedgwick  Distance and direction from	n accept town as situ	SE 1/4		1/4 NE	1/4		4	<u> </u>	27	S	R	1W	E/W	
2845 N. Sprin	-		hita, Kar	-										
2 WATER WELL C	WNER: <b>BER</b> ,BOX #: <b>2845</b>	RY, Mallory N. Springm lita, Kansas	,	1545		ZIP	CODE:	M M M I I I I		Board of Ag	riculture, Divis	ion of Wat	ter Resource	
3 LOCATE WELL'S LO		DEPTH OF COM	PLETED W	ELL:	70	ft.		ELEVATIO						
WITH AN "X" IN SEC	Dep	oth of groundwate ELL'S STATIC W	er Encounte	red: EL <b>26</b>			LAND SU	JRFACE ME	ASURE	ft. ON mo	/day/yr:	8/22/1	ft. <b>16</b>	
w Wile	NE	Est. Yield:	ump test dat gpm er 12	Well v	vater was vater was	5		ft. afte ft. afte	r	hou	s of pumpin s of pumpin	g @	gpm gpm	
2 w	WE	ore Hole Diamete ELL WATER TO Domestic 3	-	S:		to 70 pply <	ft. 7. Lawn a	and and garden	۵	in. Dewater	9	to 1. Injecti her (Sne	ft. ion well cify below)	
s	\ <sub>\</sub>	. <b>Irrigation</b> 4 las a chemical/bact omitted		6. Oil field	water s	upply	8. Air cor YES		) 10				s sample	
5 TYPE OF CAS 1. Steel	SING USED: 3. RPM (SF	•		7. Fiberglas		9. Othe	er (Specify	below)	CASING	JOINTS:	Glued Welded		hreaded Clamped	
2. PVC Blank casing diamete	> 4. ABS er <b>5</b>	in. to	os-Cement 50 ft.,	8. Concrete Dia.		in.	to	ft.,	Dia.		in.	to	ft.	
Casing height above		12 in.,		Weight:	2.35	lbs.	/ ft.	W	all thickne	ess or gau	ige No.	.214		
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)														
SCREEN OR PERFO		SS ARE:		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,					(-1	,			
1. Continuous slot			Gauzed wi	rapped		7. Torci	h cut	9.	Drilled h	oles	11. N	one ( op	en hole)	
2. Louvered shutte	er 4. Key pu	unched 6.	Wire wrap	ped		8. Saw	cut	10.	Other (s	pecify)				
SCREEN - PERFORA	TION INTERVAL	From	50	ft.	to 7	70 f	ft.,	Fro <b>m</b>		ft.		to	ft.	
		From		ft.	to	f	ft.,	From		ft.		to	ft.	
GRAVEL PA	CK INTERVALS:	From	24	ft.	to	<b>70</b> f	t.,	From		ft.		to	ft.	
		From		ft.	to	f	ft.,	From		ft.		to	ft.	
6 GROUT MATERI	ALS: 1. Neat	cement	2. Cem	ent Grout		3. E	Bentonite		Othe	er ben	tonite ho	le plus	ξ	
Grout Intervals:	From 4	ft. to	24	ft., From		ft.	to	ft., From			ft.			
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy						estock p	pens	13. Insecticide storage			15. <b>Oil</b>	15. Oil well/Gas well		
2. Sewer lines	5. Cess P		8. Sewage I	lagoon		el storaç				ater well	16. Ot	ner (spec	cify below)	
3. Watertight sewe			9. Feed yar	d	12. <b>Fer</b>	tilizer s	torage							
Direction from well?	West							Ho			ft. plus			
From To		LITHOLOGI	IC LOG		Fro	om	То		LI	THOL	OGIC LC	)G		
3 20	topsoil clay				-									
20 50	fine sand												***************************************	
50 70	medium sand													
-					+	<del></del>								
					$\top$									
											-			
					-									
					-	-								
7 Contractor's or L	andowner's Certific	cation: This water	r well was 1	construct	<b>ed</b> ) 2	. reco	nstructed	or 3.	plug	ged	under my j	urisdictio	n and	
was completed on Kansas Water Well		8/22/16		and this recor			•	knowledge a			24/16			
under the business			mp Servi			by (sign:	•				_	, ith		
	- 11mi b		Jei V			. , 5			100	w	5. Ha	MP		