	WATER WE	ELL RECOR	) Form	wwc-	5 KS	A 82a-1	212			
1 LOCATION OF WATER WELL:	FRACTION				NUMBER		HIP NUMBER	RANGE NUMBER		
- Sedgwick	SE 1/4	SE 1/4	SE 1/4	36	)	T	<b>27</b> s	R	1W	E/W
Distance and direction from nearest town or city  2510 W. Pawnee Store		Wichita, I	Kancac							
	K TRIP CORI		Kansas							
	W. Central						Board of Ag	riculture, Division		
	hita, Kansas			ZIP CO	DE:		Application Nu	mber: 2	0160	131
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPL	LETED WELL:	35	ft.	E	ELEVATION	:			
WITH AN "X" IN SECTION BOX: De	pth of groundwater	Encountered:		ft.			ft.			ft.
	ELL'S STATIC WA	TER LEVEL	14 FT.	BELOW LA	AND SUR	RFACE MEA	SURED ON mo/	day/yr: {	8/23/1	6
NW NE	Pum	np test data: V	Nell water wa	as		ft. after	hour	s of pumping (	<u>@</u>	gpm
₩ E B	Est. Yield:	01	Well water wa			ft. after		s of pumping (	_	gpm
	Bore Hole Diameter ELL WATER TO BE	12 in.		to <b>35</b>	ft.	and	in.		0 Injection	ft. <b>on well</b>
			blic water s	upply 7. I	Lawn an	d garden o	9. Dewater	<u>g</u>	•	cify below)
	2. Irrigation 4.	Industrial 6. Oil	field water	supply 8.	Air cond	itioning	10. Monitori	ing well		
	Nas a chemical/bacteri ibmitted	iological sample subm	nitted to Depart	ment? Y	YES	NO ater Well Dis		what mo/day/	/yr was NO	
	brinted			0.00				Glued		hreaded
5 TYPE OF CASING USED: 1. Steel 3. RPM (SF	R) 5. Wrought I	tron 7. Fib	erglass	9. Other (		pelow) C	ASING JOINTS:	Welded		Clamped
2. PVC 4. ABS	6. Asbestos	-Cement 8. Co	ncrete tile	SDR-26	5					, ampou
Blank casing diameter 8	in. to 2	20 ft., C	Dia.	in.	to	ft.,	Dia.	in. to		ft.
Casing height above land surface:	12 in.,	Weig	ght: <b>5.5</b> 2	2 lbs. / f	ft.	Wall	thickness or gau	ige No.	332	
TYPE OF SCREEN OR PERFORATION	N MATERIAL:		_							
Steel 3. Stainless Steel	5. Fiberglass	7. PVC		9. ABS			Other (specify)	- 11-1		
2. Brass 4. Galvanized	6. Concrete Ti	ile 8. RMF	P (SR)	10. Asbest	tos-Ceme	ent 12.	None used (oper	i noie)		
SCREEN OR PERFORATION OPENING				7 Tauch -	4	0 <b>n</b>	rilled holes	11 Nor	no ( on	en hole)
1. Continuous slot 3. Mill sl		Sauzed wrapped		7. Torch c	_			II. NON	e ( ope	in noie)
2. Louvered shutter 4. Key p	unched 6. V	Vire wrapped	(	8. Saw cu	シ	10. O	ther (specify)			
SCREEN - PERFORATION INTERVAL	From	<b>20</b> ft.	to	30 ft.,		From	ft.	to		ft.
	From	ft.	to	ft.,		From	ft.	to		ft.
GRAVEL PACK INTERVALS:	From	<b>20</b> ft.	to	35 ft.,		From	ft.	to		ft.
	From	ft,	to	ft.,		From	ft.	to		ft.
6 GROUT MATERIALS: 1. Neat	cement	2. Cement Gro	ut	3. <b>Be</b> i	ntonite		Other ben	tonite hole	plug	;
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From						From	ft.	to	ft.	
What is the nearest source of possible control of the control of t	10. <b>Li</b>	vestock per	ns	13. <b>Inse</b>	cticide storage	15. <b>Oil w</b>	15. Oil well/Gas well			
2. Sewer lines 5. Cess I	11. Ft				Abandon water well 16. Other (specify below)					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparel								arent		
Direction from well?						How	many feet?			
From To	LITHOLOGIC	LOG	F	rom -	То		LITHOL	OGIC LOC	}	
0 3 topsoil										
3 12 clay and shal 12 28 fine sand	<u>e</u>									
28 35 medium sand	d									
					-+					
	****									
7 Contractor's or Landowner's Certif	ication: This water	well was 1. cons	structed	2. recons	structed	or 3.	plugged	under my juri	isdictio	n and
was completed on (mo/day/year)	8-23-16	and this	record is tru	e to the bes	t of my kı	nowledge ar	d belief.			
Kansas Water Well Contractor's Licen	nse No. 236	This	water well red	cord was cor	mpleted (	on (mo/day/s	vear) 8/2	5/2016		
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										