WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NWSedgwick NW 1/4 NW1/4 1/4 Т 27 S 1W Ε/W Distance and direction from nearest town or city street address of well if located within city? 2908 N. Curtis Wichita, Kansas H & H HOMEBUILDERS INC. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 3906 N. Lakecrest ZIP CODE: 67205 Wichita, Kansas CITY, STATE: Application Number: 40 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Well water was Pump test data: ft. after hours of pumping @ gpm -NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm ≌ Bore Hole Diameter 12 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES Was Water Well Disinfected? NO submitted 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 30 Dia. ft.. Dia ft, Blank casing diameter in. to to in. to 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9. ABS 1 Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 1. Continuous slot 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 30 40 From to ft. From ft ft. to ft. From From to ft.. ft. ft. to 24 **GRAVEL PACK INTERVALS:** ft to 40 From From ft., ft. From ft. to ft., From ft to ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft 24 ft., From ft. From ft. to ft., What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 7. Pit privy 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit North How many feet? 40 ft. plus Direction from well? LITHOLOGIC LOG From Τо ITHOLOGIC LOG From To A topsoil 3 8 clay 15 fine sand 8 15 40 medium sand under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. 3/17/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/20/17

under the business name of Harp Well and Pump Service by (signature)

Todd S. Harp