WATER WELL RECORD	Form WV	VC-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL: FRACTION		SECTION NUMBER TOWNSHIP NUMBER			RANGE NUMBER	
Sedgwick NE 1/4 SE 1/4 SW	1/4	18	<u> 7</u> 2	27 s	R 1W	Ε/W
Distance and direction from nearest town or city street address of well if located within city? 821 N. Covington St. Wichita, Kansas						
2 WATER WELL OWNER: MILLSPAUGH, Jeff						
RR#,ST. ADDRESS,BOX #: 821 N. Covington St.				Board of Agr	iculture, Division of Wa	ter Resource
CITY, STATE: Wichita, Kansas	Z	P CODE:		Application Nur	nber:	
	15 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered:	ft,			ft.	7/24/	17 ft.
WELL'S STATIC WATER LEVEL 30	FT. BELO	W LAND SL	IRFACE MEAS	URED ON mo/	day/y r.	
	ater was		ft. after	hours	s of pumping @	gpm
	ater was	115 0	ft. after		s of pumping @	gpm
Bore Hole Diameter 12 in. WELL WATER TO BE USED AS:	to 1	115 ft.	and	in.	to _{ina} 11. Inject	ft, ion um!!
	ater supply	Z. Lawn a	nd garden on	9. Dewateri	ing 12. Other (Spe	
2. Irrigation 4. Industrial 6. Oil field v	vater supply	8. Air con	ditioning	10. Monitori	ng well	
S Was a chemical/bacteriological sample submitted to submitted	Department?	YES	NO NO		what mo/day/yr wa	=
TYPE OF CASING USED:			Vater Well Disir			
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	•	ther (Specify	below) CA	SING JOINTS:		Threaded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete 9	tile SD	R-26			Weided	Siampeu
Blank casing diameter 5 in. to 95 ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight:	2.35 II	bs. / ft.	Wall t	hickness or gau	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:						
The state of the s						
2. Brass 4. Galvanized 6. Concrete Tite 8. RMP (SR)	10. A	sbestos-Cen	nent 12. N	one used (open	hole)	
SCREEN OR PERFORATION OPENINGS ARE:					44.11	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped		rch cut		iled holes	11. None (op	en hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Sa	w cut	10. Oti	ner (specify)		
SCREEN - PERFORATION INTERVAL From 95 ft. to	115	ft.,	From	ft.	to	ft.
From ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From 24 ft. to	0 115	ft.,	From	ft.	to	ft.
From ft. t	0	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	:	3. Bentonite		Other bent	onite hole plug	3
Grout Intervals: From 4 ft. to 24 ft., From	ft.	to	ft.,	From	ft. to	ft,
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestoc	k pens	13. Insec	ticide storage	15. Oil well/Ga	s well
2, Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)						
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well? North		_	How m	any feet? 10	ft. plus	
From To LITHOLOGIC LOG	From	То		LITHOLO	OGIC LOG	
0 3 topsoil		ļ				
3 20 clay 20 42 fine sand	+	-				
42 95 clay	 					
95 115 medium sand						
	 					
	+	 				
		<u> </u>				

	 	† †			· · ·	
Contractor's or Landowner's Certification: This water well was 1. constructed	d) 2. re	constructed	or 3.	plugged	under my jurisdictio	n and
was completed on (mo/day/year) 7/24/17 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/26/17						
under the business name of Harp Well and Pump Service by (signature) Todd S. Howh						