WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER FRACTION TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE SE NE 30 1/4 1/4 1/4 Т 27 1WE/W Distance and direction from nearest town or city street address of well if tocated within city? 10429 Hidden Valley Wichita, Kansas WATER WELL OWNER: **HAMPTON**, Doyle Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10429 Hidden Valley Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 158 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. N 20 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was NE ft. after hours of pumping @ gpm NW Est. Yield: Well water was ft. after map hours of pumping @ gpm 12 to 148 ≌ Bore Hole Diameter ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-3. Feedlot 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample (NO) Was a chemical/bacteriological sample submitted to Department? submitted YES Was Water Well Disinfected? 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: CGlued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 138 Dia. in. Dia. ft. to in to 2.35 Casing height above land surface: in. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 138 158 From ft to ft., From ft ft. to ft. From to ft., From ft ft. to GRAVEL PACK INTERVALS: 24 ft 158 to From ft., From ft. to ft. From ft. to ft.. From fŧ to ft. **GROUT MATERIALS:** Other 6 bentonite hole plug Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: 24 ft.. fi ft., to From to ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privv 13. Insecticide storage 15 Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line South Direction from well? How many feet? 50 ft. plus LITHOLOGIC LOG From Tο From Tο LITHOLOGIC LOG topsoil 20 <u>clay</u> 20 fine sand 75 clay 45 75 105 fine sand 105 130 ciav 130 158 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, under my jurisdiction and 7/11/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/13/17 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb