WATER WELL RECORD Form WWC-5 KSA 82a-1212														
1 LOCATION OF WATE	R WELL:	FRACTION					ON NUMBE				RANGE NUMBER			
Sedgwick			/4 SW	1/4 N	W 1/4	L	2	Т	27	S	R	1W	E/W	
Distance and direction from 2920 N. Curt		-		within city?										
2 WATER WELL		<u>ichita, Kansas</u> EREZ, Ramor												
RR#,ST. ADDRESS		920 N. Curtis	•						Во	ard of Agri	culture, Divisi	on of Wa	er Resource	
CITY,	STATE: W	Vichita, Kansa	S			ZIP	CODE: 6	7205	Appli	cation Num	nber:			
3 LOCATE WELL'S L	OCATION	4 DEPTH OF CO	MPLETED \	WELL:	40	ft.		ELEVATIO	N;					
WITH AN "X" IN SE	CTION BOX:	Depth of groundwa	ater Encount	tered:		ft.				ft.			ft.	
	:	WELL'S STATIC	WATER LEV	VEL 10	FT. I	BELOV	V LAND S	URFACE ME	ASURED	ON mo/d	lay/yr:	10/13/	17	
I NW	- NE		Pump test d	ata: Well	water was	\$		ft. after		hours	of pumping	@	gpm	
₩ X	' <u> </u>	Est. Yield:	gpm	•	water was		<b>n</b>	ft. afte			of pumping		gpm	
<u></u>		Bore Hole Diame		****		to 4(	D ft	. and		in.	11	to I. Injecti	ft.	
sw	SE	1. Domestic	3. Feedlot		water su	pply <	7. Lawn	and garden	only 9. I	Dewaterii	я	-	cify below)	
		2. Irrigation	4. Industria	al 6. Oil fiel	d water s	upply	8. Air co	nditioning	10. 1	Monitorin	ng well			
S	-	Was a chemical/basubmitted	acteriological s	ample submitted	I to Departm	nent?	YES	NO Water Well D			vhat mo/da	y/yr wa: <b>NC</b>	•	
5 TYPE OF CAS	SING USED:					0.04					Glued		hreaded	
1. Steel	3. RPM	1 (SR) 5. Wrou	ght Iron	7. Fibergla	ass		ner (Specify	y below)	CASING J	OINTS: C	Welded		Clamped	
2. PVC	> 4. ABS	6. Asbe	stos-Cement	t 8. Concre	te tile	SDR	26					`	Diamped	
Blank casing diamet	er <b>5</b>	in. to	30 ft	t., Dia.		in.	to	ft.,	Dia.	i	in. 1	io	ft.	
Casing height above	e land surface:	<b>12</b> in.	,	Weight:	2.35	lbs	s. / ft.	Wa	all thicknes	s or gaug	je No.	.214		
TYPE OF SCREEN				7.51/0			_		011					
	3. Stainless Ste			7. PVC	D)	9. AB	_		Other (sp		h-1-\			
	4. Galvanized	6. Concret	ie riie	8. RMP (S	K)	10. AS	bestos-Ce	ment 12	2. None use	ea (open	noie)			
SCREEN OR PERFO			5. Gauzed v	vrannod		7. Toro	ch cut	0	Drilled hol	loe	11 No	ne ( on	en hole)	
					_						11.140	пе ( ор	ii iioie;	
2. Louvered shutte			6. Wire wra			8. Saw		10.	Other (spe	есіту)				
SCREEN - PERFORA	ATION INTERV		30	ft.		40	ft.,	From		ft.	t	0	ft.	
	******	From	24	ft.	to	40	ft.,	From		ft.	t	0	ft.	
GRAVEL PA	CK INTERVAL	S: From	24	ft.		10	ft.,	From		ft.	t	0	ft.	
		From		ft.	to		ft.,	From		ft.		0	ft.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plu										e plug				
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:						ft.	to	ft., From			ft. to ft.			
1. Septic tank	7 Dit pring							13. Insecticide storage 15. Oil well/Gas well				well		
2. Sewer lines	5. <b>Ce</b>	ss Pool	8. Sewage	alagoon	11. Fue	el stora	age	14. <b>Ab</b>	andon wa	ter well	16. Oth	er (spec	ify below)	
3. Watertight sewe		epage pit	9. <b>Feed ya</b>	ard	12. <b>Fer</b>	tilizer	storage							
Direction from well? North						From To			How many feet? 50 1					
From To	topsoil	LITHOLOG	JIC LUG		Fre	om	То		LII	HOLO	GIC LO	G		
3 6	clav				$\dashv$			· · · · · · · · · · · · · · · · · · ·						
6 15	fine sand													
15 40	medium sa	and												
					-	_								
					<u> </u>	_								
													-	
						$\neg$								
					_									
								<u></u>						
		ertification: This wa				•	onstructed		plugge	ed t	under my ju	risdictior	and	
was completed on	(mo/day/year)	10/13/1	1	and this reco	ord is true	to the b	best of my	knowledge a	and belief.					
Kansas Water Wel	Contractor's Li	icense No. 236		This water	r well reco	rd was	completed	d on (mo/day			6/17			
under the business	name of Ha	rp Well and P	ump Serv	vice	1	by (sigr	nature)		$T \sim J$	2,5	$\mathcal{H}_{\alpha}$	vh		