	WATER WELL RE	CORD F	orm WW	C-5 K	SA 82a-1212				
1 LOCATION OF WATER WELL:	FRACTION		SECT	ION NUMBER	TOWNSHIP NU	MBER	RANGE NUM	IBER	
- Sedgwick	NW 1/4 NW	1/4 NE	1/4	23	т 27	S	R 1W	E/W	
Distance and direction from nearest town or city street address of well if located within city?									
504 N. Baehr Wichita, Kansas									
2 WATER WELL OWNER: MEN	ONITE HOUSING								
	N. Topeka					Board of Agric	ulture, Division of Wal	ter Resource	
CITY, STATE: Wichi	ita, Kansas		ZIF	CODE: 6	7204 Ap	plication Num	ber:		
3 LOCATE WELL'S LOCATION 4 D	EPTH OF COMBE	FIL: 30			ELEVATION:				
			ft.			ft.		ft.	
	th of groundwater Encounte						. 0/0//		
	LL'S STATIC WATER LEVE			W LAND SU	JRFACE MEASURE			17	
NW NE	Pump test dat	ta: Well wate	er was		ft. after		of pumping @	gpm	
₩	Est. Yield: gpm	Well wate	er was		ft. after	hours	of pumping @	gpm	
≥ w = Bo	ore Hole Diameter	in.	to	ft.	and	in.	to	ft.	
	WELL WATER DE USED AS: 9. Dewatering 11. Injection well 1. Domestic 3. Feedlot 5. Public water supply Lawn and garden only 12. Other (Specify below)								
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/barteriological sample submitted to Department? VES NO ; if yes, what mo/day/yr was sample									
, , , , , , , , , , , , , , , , , , ,	as a chemical/bacteriological sar mitted	mple submitted to D	epartment?	YES Was V	NO Vater Well Disinfecte				
	milleo								
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASING	JOINTS:		Threaded	
Weided Clamped									
2. PVC 4. ABS					4				
Blank casing diameter 1 1/4 in		, Dia.	in.	to	ft., Dia.	i	n. to	ft.	
Casing height tool and surface: 36 in., Weight: Ibs. / ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)									
2. Louvered shutter 4. Key pu	inched 6. Wire wrap	ped	8. Sav	wcut	10. Other (s	pecify) N/	A		
SCREEN - PERFORATION INTERVAL	From	ft. to		ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:		ft. to		-					
GRAVEL PACK INTERVALS.	From			ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat c	ement 2. Cem	ent Grout	3	Bentonite	Oth	er bento	onite hole plug	g	
Grout Intervals: From ft. to ft., From ft. to ft., From 3 ft. to 30 ft.									
What is the nearest source of possible contamination:									
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well									
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)									
2 Section and 12 Sections									
3. Watertight sewer line 6. Seepage pit 9. reed yard 12. reruizer storage How many feet?									
	ITHOLOGIC LOG		From	То			GIC LOG		
			0		compacted ton		010 200		
			3		bentonite hole				
						hine			
				l					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year)	9-26-17				knowledge and belie	f			
				-	-		- /1		
Kansas Water Well Contractor's Licens	e No. 236	This water we	Il record wa	s completed	i on (mo/day/year)	9/2'	7/17		
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									