WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 NW Sedgwick NW 1/4 Т 27 S 1WE/W Distance and direction from nearest town or city street address of well if located within city? 2909 Gulf Breeze Wichita, Kansas WATER WELL OWNER: NIES CONSTRUCTION Board of Agriculture, Division of Water Resource 10333 E. 21st N. #303 RR#,ST. ADDRESS,BOX #: CITY, STATE Wichita, Kansas Application Number: ZIP CODE 35 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **ELEVATION** WITH AN "X" IN SECTION BOX: 2/5/18 ft. Depth of groundwater Encountered: ft. ft. 10 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Well water was NW Pump test data: ft. after hours of pumping @ NE gpm Est. Yield: Well water was ft. after hours of pumping @ gpm Ī Bore Hole Diameter 12 to 35 ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO (YES) submitted Was Water Well Disinfected? 5 TYPE OF CASING USED 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter to 25 Dia ft., to Dia. ft. in. to 12 2.35 Casing height above land surface: in., Weight: lbs. / ft. Wall thickness or gauge No .214 TYPE OF SCREEN OR PERFORATION MATERIAL 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 8. RMP (SR) 12. None used (open hole) 2 Brass Concrete Tile 10. Asbestos-Cement 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1 Continuous slot 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 25 35 From to ft., From to ft ft. to From ft.. From ft. to 24 ft **GRAVEL PACK INTERVALS:** to 35 From ft., From to ft. ft. From to ft From ft. ft **GROUT MATERIALS** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. 24 ft., From ft. to ft., From to ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15 Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3 Watertight sewer line How many feet? 50 ft. plus Direction from well? LITHOLOGIC LOG From LITHOLOGIC LOG From Τо Τо topsoil 3 clay 6 6 15 fine sand 15 35 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3. under my jurisdiction and 2/5/18 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 2/7/18

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp