WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 NW NWSedgwick 2 27 1W1/4 1/4 T S E/W Distance and direction from nearest town or city street address of well if located within city? 2968 N. Gulf Breeze Ct. Wichita, Kansas WATER WELL OWNER: **SHARP HOMES** Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2131 N. Collective Ste. #A ZIP CODE: 67205 Wichita, Kansas CITY, STATE: Application Number 35 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 1/27/18 ft. Depth of groundwater Encountered: 8 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data Well water was ft. after hours of pumping @ NW NFgpm Est. Yield: apm Well water was ft. after hours of pumping @ gpm Ξ 12 to 35 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only S₩ SE 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 26 Dia. Dia in. ft. 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 3. Stainless Steel 1. Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 10. Other (specify) 35 SCREEN - PERFORATION INTERVAL 26 ft From to ft., From ft. to ft From to ft., From to ft. 26 **GRAVEL PACK INTERVALS:** to 35 ft.. From From ft. From ft. to ft., From ft. to ft. **GROUT MATERIALS:** Other bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite Grout Intervals: From 24 ft., ft. to ft., From ft What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage ③ Watertight sewer line 6. Seepage pit West Direction from well? How many feet? 20 ft. plus LITHOLOGIC LOG LITHOLOGIC LOG From Τo From To topsoil 6 clay fine sand 6 medium sand

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 1/27/18 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/31/18

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp