WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER 1/4 NW  $\mathbf{SW}$ Sedgwick 1/4 NW1/4 2 Т 27 S 1WE/W Distance and direction from nearest town or city street address of well if located within city? 29th N. and Hoover, 1/8 South and 500' East Wichita, Kansas (2 construct on 1 permit) WATER WELL OWNER: WICHITA, CITY OF Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 455 N. Main 20180055 CITY, STATE: Wichita, Kansas ZIP CODE Application Number: 30 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION** WITH AN "X" IN SECTION BOX Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 11 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was -NW NE: ft. after hours of pumping @ apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm 12 Ξ Bore Hole Diameter to 30 and in. ft. WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well SW SE 7. Lawn and garden only 3. Feedlot 5. Public water supply 12. Other (Specify below) 8. Air conditioning 4. Industrial 6. Oil field water supply 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample (NO) S Was a chemical/bacteriological sample submitted to Department? submitted Was Water Well Disinfected? (YES NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: C Glued 7. Fiberglass Threaded 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4 ABS 8 Blank casing diameter in. 20 ft.. Dia. to ft., Dia in to ft 12 Casing height above land surface: in.. 5.52 Weight: lbs. / ft. Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass Concrete Tile 8. RMP (SR) 4 Galvanized 12. None used (open hole) Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 20 ft 30 From to ft., From ft. From ft. to ft., From to ft. 20 GRAVEL PACK INTERVALS: ft. From to 30 ft., From ft. to ft. ft. From to ft.. From ft. GROUT MATERIALS: Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From ft. ft.. From 0 to 20 ft. to ft., From ft. ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privv 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines None 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? From То LITHOLOGIC LOG From Τо LITHOLOGIC LOG topsoil 3 6 sandy & dirt 20 6 fine sand 20 30 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 3/9/2018 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/12/18 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb