WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NWSWSedgwick 1/4 SE 1/4 2 Т 27 S R 1W E/W Distance and direction from nearest town or city street address of well if located within city? 2420 N. Paradise Ct. Wichita, Kansas WATER WELL OWNER: CRAFT, Dennis Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1313 N. Maize Rd. #1409 Wichita, Kansas ZIP CODE: 67212 CITY, STATE Application Number: 35 4 DEPTH OF COMPLETED WELL: ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was NW ΝE ft. after hours of pumping @ gpm Est. Yield: apm Well water was ft. after hours of pumping @ gpm ≅w Bore Hole Diameter 12 to 35 ft. WELL WATER TO BE USED AS: 11. Injection well < se 9. Dewatering 5. Public water supply 7. Lawn and garden only 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO (YES) submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: C Glued Threaded 5. Wrought Iron Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 26 ft., Dia. Dia ft. in to 12 Casing height above land surface: 2.35 in.. Weight: lbs. / ft. Wall thickness or gauge No .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 9. ABS 11. Other (specify) 1. Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 26 ft. 36 to ft., From From ft ft. to ft From to ft., From ft ft to 24 ft GRAVEL PACK INTERVALS: to 36 From ft., From to ft From ft. to ft.. From ft ft. **GROUT MATERIALS:** 6 Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From ft. to ft.. From fŧ 4 to 24 ft., From to ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit West Direction from well? How many feet? 70 ft. plus From From Τо LITHOLOGIC LOG Τo LITHOLOGIC LOG topsoil 3 6 clav 6 21 fine sand medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 3/8/18 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/12/18

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb