WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE 1/4 SW 1/4 NE 1/4 24 Т 27 S 1W E/W Distance and direction from nearest town or city street address of well if located within city? 3020 W. 2nd Wichita, Kansas TURNER, Linda WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: P.O. Box 636 Andover, Kansas CITY, STATE: Application Number 4 DEPTH OF COME GO WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: ft. MEASURED ON mo/day/yr: WELL'S STATIC WATER LEVEL FT. BELOW Well water was Pump test data: ft. after hours of pumping @ NE NW Est. Yield: Well water was ft. after hours of pumping @ apm Φ Ξ Bore Hole Diamete and ft. WELL WATER THE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 12. Other (Specify below) 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample (NO) Was a chemical/bacteriological sample submitted to Department? (YES) submitted Was Water Well Disinfected? NO TYPE OF CASING USED: **CASING JOINTS:** Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) Steel Welded Clamped 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 8" Blank casing diameter Dia. ft.. Dia. to to in to ft. Casing height serve land surface: 15' Weight: Wall thickness or gauge No. lbs. / ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1 Steel 12. None used (open hole) 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 9. Drilled holes 11. None (open hole) 1. Continuous slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL ft . From From to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: to ft., From From ft. to ft. ft. From to ft.. From ft. Other **GROUT MATERIALS** 2 Cement Grout 3 Bentonite 1. Neat cement Grout Intervals: 15 ft. 15.5 ft., From From 25 17 ft. ft., From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? Direction from well? From LITHOLOGIC LOG From Τo LITHOLOGIC LOG concete pit 3'X3'X15' 0 151 15.5 concreted floor flat 15.51 gravel installed) 18 bentonite hole plug to botton of 2' pine surrouning 8" casing 20 bentonite hole plug in 8" casing to bottom

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/10/18 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/12/18

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp