		WATER	WELL	RECO	ORD F	orm W	WC-5	KSA 82a	a-1212				
1 LOCATION OF WATE	FRACTION				SE	CTION NUMB	BER TOV				RANGE NUMBER		
Sedgwick			1/4 NV			1/4	11	T	27	S	R	1W	E/W
Distance and direction fro 5339 W. 21st		ichita, Kan		ed within	city?								
2 WATER WELL O		X MACHIN							-,				
RR#,ST. ADDRESS	- · · · · · · · · · · · · · · · · · · ·	W. 21st N	_							Board of Ag	griculture, Divisi	on of Wat	er Resource
CITY,	STATE: Wic	hita, Kansa	ıs				ZIP CODE:	67205	Ap	plication Nu	ımber:		
3 LOCATE WELL'S LO	OCATION 4	DEPTH OF CO	MPLETED	WELL	: 4	0 f	t.	ELEVAT	ION:				
WITH AN "X" IN SEC		pth of groundw	ater Encou	untered:			ft.			ft.			ft.
X	· w	'ELL'S STATIC	WATER L	EVEL	12	FT. BE	OW LAND	SURFACE N	//EASURE			6/14/1	18
NW NW	- NE	=	Pump test		Well wa			ft. af			rs of pumping		gpm
w ⊠ie		Est. Yield: Bore Hole Diam		m 12	Well wa		40	ft. af ft. ar	ter nd	nou in.	rs of pumping	to	gpm ft.
- "	' I I	ELL WATER T		D AS:						Dewate	rina 11	. Injecti	
sw	SE: -: 1	1. Domestic	3. Feedle	ot 5	. Public wa	iter suppl	y 7. Lawr	n and garde	n only		12. Ot h	-	cify below)
		2. Irrigation	4. Indust				oly 8. Air c		_). Monitor	i <mark>ng well</mark> , what mo/da	www.wa	e cample
s		Was a chemical/b ubmitted	acteriologica	il sample	submitted to	Department		No.			YES	y/yi wa:	
5 TYPE OF CAS	SING USED:	5 \Mro.	ight Iron	7	. Fiberglass	9.	Other (Spec	ify below)	CASING	JOINTS:	Glued	Т	hreaded
1. Steel	3. RPM (S	R)	ught Iron		J	C	DR-26	,,			Welded	(Clamped
2. PVC	> 4. ABS		stos-Ceme		. Concrete t	ile -							_
Blank casing diamete		in. to	30	ft.,	Dia.	in.	to	ft.,	Dia	•	in. t	0	ft.
Casing height above		12 in	.,	1	Weight:	2.35	lbs. / ft.	١	Wall thickn	ess or ga	uge No.	.214	
1. Steel	OR PERFORATION 3. Stainless Steel	N MATERIAL: 5. Fibergi	255	7	PVC	q	ABS		11. Other	(specify)			
	Galvanized	6. Concre		_	RMP (SR)	-	Asbestos-C		12. None		n hole)		
SCREEN OR PERFO		GS ARE:			` '					, ,	,		
1. Continuous slot			5. Gauzeo	d wrapp	ed	7.	Forch cut	9	9. Drilled I	noies	11. No	ne (ope	en hole)
2. Louvered shutte	er 4. Keyp	unched	6. Wire w	rapped		<u>8</u> .	Saw cut	10	0. Other (s	specify)			
SCREEN - PERFORA	•	From	30	• •	to	- 40	ft.,	From	,				
JOOKELN -1 EKT OK	KIION IIN I ERVAE	From	30	ft.	to		ft.,	From		ft.		0	ft.
GRAVEL PA	CK INTERVALS:	From	24		to		ft.,	From		ft. ft.		o o	ft.
		From		ft.	to		ft.,	From					ft.
6 GROUT MATER	IAIS:					·			Oth	ft.		0	ft.
Grout Intervals:	From 4	cement ft.	to 24	Cement ft.,	From		3. Bentoni			ben	tonite hol	to to	ft.
What is the nearest source of possible contamination:													
1. Septic tank 4. Lateral lines										secticide storage 15. Oil well/Gas well handon water well 16. Other (specify below)			
2. Sewer lines	5. Cess l		8. Sewa	•		11. Fuel s	-	14. A	Abandon v	water wel	10.00	ei (spec	ily below;
3. Watertight sewe	er line 6. Seepa West	age pit	9. Feed	yard		12. Fertili	zer storage		low monu	faata 50	ft plus		
From To		LITHOLO	GIC I O	G		Fron	1 To				ft. plus OGIC LO	G	
0 3	topsoil	LITTIGEO	0.0 20			1	- - 0 		_	IIIIOL	<u>0010 LO</u>		
3 24	fine sand]							
24 40	medium sand	<u> </u>				 							
		**			79.0	 		-					
	77-20-2												
	<u> </u>					+		+					
						 		 					
						+		+	 -				
						+	+	+					
7 Contractor's or I	_andowner's Certif	ication: This w	ater well w	as 1 (onstructor	2.	reconstruct	ed or (3 pluc	ged	under my ju	risdiction	n and
was completed on		6/14/1				_	he best of m			-			-
			_					_			10/10		
Kansas Water Well					nis water w		was complete	ea on (mo/di			18/18		
under the business	name of Harp	Well and I	'ump Se	ervice		by	(signature)		Too	ad S	S. Ha	rp	