WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER FRACTION TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE  $\mathbf{s}\mathbf{w}$ 1/4 1/4 NW 1/4 Т 27 S R 1W E/W Distance and direction from nearest town or city street address of well if located within city? 2726 N. Curtis Wichita, Kansas WATER WELL OWNER: NIES CONSTRUCTION Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. #303 Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 36 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. N WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/vr: 3/14/19 Pump test data: Well water was NEft. after hours of pumping @ apm Est. Yield: Well water was ft. after hours of pumping @ gpm Ξ̈́۷ Bore Hole Diameter 12 to 36 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE-5. Public water supply 7. Lawn and garden only 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 26 to ft.. Dia. to Dia in. ft. 12 Casing height above land surface: in.. Weight: 2.35 Wall thickness or gauge No. lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL From 36 to ft., From ft. to From ft. to ft., From to ft. GRAVEL PACK INTERVALS: 24 ft. 36 From ft.. From ft ft. From ft. to ft., From ft. to ft. **GROUT MATERIALS:** 6 1. Neat cement 2. Cement Grout Other bentonite hole plug 3. Bentonite Grout Intervals: From 4 ft. 24 ft., From ft. to From ft What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 3. Watertight sewer line 9. Feed yard 12. Fertilizer storage 6. Seepage pit Direction from well? West How many feet? 40 ft. plus From Τо LITHOLOGIC LOG From To LITHOLOGIC LOG topsoil sandy soil 24 fine sand 24 36 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and 3. plugged was completed on (mo/day/year) 3/14/19 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/15/19 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb