·	WATER W	<u>ELL R</u> E	ECOF	RD Fo	orm WV	VC-5 K	(SA 82a-1)			
1 LOCATION OF WATER WELL:	FRACTION									
- Sedgwick	SW 1/4	NE	1/4	NW	1/4	2	Т	27 S	RI	W E/W
Distance and direction from nearest town or city			within city	y?						
2928 N. Curtis	Wichita, Kar	isas								
	RP HOMES	~						Board of A	griculture, Division o	f Water Resource
****	N. Collective	Ste. #A	•		_					
	nita, Kansas				_	P CODE:		Application N		
WITH AN "X" IN SECTION BOX:	DEPTH OF COMP pth of groundwater			36	ft.		ELEVATION	: ft.		ft.
	ELL'S STATIC WA			8	FT. BELC	W LAND SU	URFACE MEA	SURED ON mo	/day/yr: 4/	3/19
NWNE		mp test da		Well wate			ft. after		rs of pumping @	gpr
	Est. Yield:	gpm		Well wate			ft. after	hou	irs of pumping @	gpm
₩ ₩ ₩ E B	ore Hole Diameter	· 12	2 in	n.	to .	36 ft.	. and	in.	to	ft.
	ELL WATER TO B	E USED A	AS:					9. Dewate	ring 11. In	jection well
	. Domestic 3.	Feedlot	5. F	Public wat	er supply	C7. Lawn a	and garden o			Specify below
	-	Industria		Oil field wa	•••		nditioning	10. Monito	ring well , what mo/day/yr	wae samolo
J. J	Vas a chemical/bacter Ibmitted	nological sa	ample su	bmitted to De	epartment?	YES	(NO) Water Well Dis		YES	NO
					_				\geq	Threaded
5 TYPE OF CASING USED: 1. Steel 3. RPM (SF	5. Wrought	Iron	7. F	iberglass		ther (Specify	y below) C	ASING JOINTS	\sim	
2. PVC 4. ABS	6. Asbestos	s-Cement	8. C	Concrete tile	_e SD	R-26			Welded	Clamped
Blank casing diameter 5		26 ft.		Dia.	in.	to	ft.,	Dia.	in. to	ft.
• •••• • ••••••••••••••••••••••••••••	10	<i></i>								
Casing height above land surface:	,		W	eight:	2.23	bs. / ft.	Wall	thickness or ga	uge No21	.4
TYPE OF SCREEN OR PERFORATION 1. Steel 3. Stainless Steel		C	7. P	VC	9. A	RS	11.	Other (specify)		
	 5. Fiberglass 6. Concrete T 	Tilo N		MP (SR)		Asbestos-Ce		None used (ope	n hole)	
2. Brass 4. Galvanized	6. Concrete 1	lie	0. K		10.7	15065105-06				
SCREEN OR PERFORATION OPENING									44 None	(anan hala)
1. Continuous slot 3. Mill sl	lot 5. 0	Gauzed w	/rapped	d	7. To	orch cut	9. D	rilled holes	11. NORE	(open hole)
2. Louvered shutter 4. Key p	unched 6. V	Wire wrap	pped		(8. S	w cut	10. O	ther (specify)		
SCREEN - PERFORATION INTERVAL	From	26	ft.	to	36	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24	ft.	to	36	ft.,	From	ft.	to	ft.
GNAVEL I AGN INTERVAES.		21		-	50					
	From		ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat	cement	2. Cen	nent G	rout		3. Bentonite	Ð	Other ber	ntonite hole p	Ç
Grout Intervals: From	ft. to		ft.,	From	ft.	to	ft.,	From	4 ft. 1	to 24 ft.
What is the nearest source of possible of 1. Septic tank 4. Latera	7	. Pit privy	,	10	0. Livesto	ck pens	13. Inse	cticide storage	15. Oil wel	I/Gas well
		Sewage		n 1	1. Fuel sto	rage	14 Aha	- ndon water we	II 16. Other (specify below
2. Sewer lines 5. Cess I		_	-			-				
3. Watertight sewer line 6. Seepa Direction from well? West	ige pit 9	. Feed ya	ra	1.	2. Fertilize	i storage	Ночи	many feet? 50) ft plus	
		21.00			Erom	То	T		OGIC LOG	
	LITHOLOGIC	LUG			From	10				
0 3 topsoil 3 6 clay										
6 15 fine sand						1	-			
15 36 medium sand	1									
						<u> </u>				
		·····				+				
						+				
						+				
						4				
h						+	1			
					1	1				
	laadlaat This (1		<u> </u>		d or 0	nlugged	under my juriso	liction and
Contractor's or Landowner's Certif		well was			-	econstructe		plugged	under my junsu	
was completed on (mo/day/year)	4/3/19		and ti	his record i	s true to th	e best of my	/ knowledge ar	nd belief.		
Kansas Water Well Contractor's Licer	nse No. 236		Thi	is water we	ll record w	as complete	d on (mo/day/y	/ear) 4	/4/19	
under the business name of Harp	Well and Pur	nn Ser	vice		by (s	ignature)	-	LAT.	S. Har	ħ
Line in cashiot have of harp	······································				- 7 (-			Jum	5. 1100	۲