

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 NW 1/4 NW 1/4	SECTION NUMBER 2	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W
---	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
4909 W. Wavcrest Wichita, Kansas

2 WATER WELL OWNER: RR#.ST. ADDRESS,BOX #: CITY, STATE:	SHARP HOMES 2131 N. Collective Ste. #A Wichita, Kansas	Board of Agriculture, Division of Water Resource Application Number: ZIP CODE: 67206
--	---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>	4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: Depth of groundwater Encountered: _____ ft. WELL'S STATIC WATER LEVEL 7 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/21/19 Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm Est. Yield: gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm Bore Hole Diameter 12 in. to 35 ft. and _____ in. to _____ ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO
---	--

5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 7. Fiberglass 6. Asbestos-Cement 8. Concrete tile	9. Other (Specify below) CASING JOINTS: Glued Threaded Welded Clamped	SDR-26
Blank casing diameter 5 in. to 25 ft., Dia. _____ in. to _____ ft.	Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)			
SCREEN - PERFORATION INTERVAL From 25 ft. to 35 ft., From _____ ft. to _____ ft.			
GRAVEL PACK INTERVALS: From 24 ft. to 35 ft., From _____ ft. to _____ ft.			

6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From _____ ft. to _____ ft.	1. Neat cement 2. Cement Grout 3. Bentonite 4. Lateral lines 7. Pit privy 10. Livestock pens	Other bentonite hole plug 13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)
What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line 4. Cess Pool 5. Seepage pit 6. Feed yard 9. Feed yard 12. Fertilizer storage		How many feet? 70 ft plus

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	23	fine sand			
23	35	medium sand			

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/21/19 and this record is true to the best of my knowledge and belief.	This water well record was completed on (mo/day/year) 3/25/19
Kansas Water Well Contractor's License No. 236 under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp