	WATER WELL	L RECORD F	orm WW	/C-5 K	SA 82a-1212	2		
1 LOCATION OF WATER WELL:	FRACTION		- 1	ION NUMBER	i .		RANGE NUM	
Sedgwick		W 1/4 NW	1/4	2	T 27	S	R 1W	E/W
Distance and direction from nearest town or city street address of well if located within city?  2988 Gulf Breeze Circle  Wichita, Kansas								
2 WATER WELL OWNER SHARP CONSTRUCTION								
RR# ST. ADDRESS.BOX #: 2131 N. Collective Ste# A								
CITY, STATE: Wichi	ta, Kansas			CODE: 6		Application Num	ber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	EPTH OF COMPLET	ED WELL: 36			ELEVATION:	_		
N Dept	h of groundwater End	4.6	ft.			ft.	(/39/	ft.
	L'S STATIC WATER			W LAND SU	RFACE MEASUF		ay/yr: 6/28/ of pumping @	gpm
NW- NE		est data: Well wate gpm Well wat			ft. after ft. after		of pumping @	gpm
₩ E Bo	re Hole Diameter	12 in.	to 3	6 ft.	and	in.	to	ft.
_   WEI	LL WATER TO BE US	SED AS:			nd mandam ambi	9. Dewaterir	•	
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)  2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample								
· · · · · · · · · · · · · · · · · · ·	mitted	-		Was V	Vater Well Disinfe	cted?	YES N	0
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASII	NG JOINTS: C		Threaded
1. Steel 3. RPM (SR) Welded Clamped  2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile								
	n. to <b>26</b>	ft., Dia.	in.	to	ft., D	ia. i	in. to	ft.
Casing height above land surface:	12 in.,	•		os. / ft.		kness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole)								
2. Louvered shutter 4. Key pu		wrapped				(specify)		
SCREEN - PERFORATION INTERVAL		26 ft. to	36	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	ft. to <b>24</b> ft. to	36	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	110111			ft.,	From	ft.	to	ft.
O COULT MATERIALS	From	ft. to		ft.,	From	ft.	to	ft.
Grout Intervals: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug  Grout Intervals: From ft. to ft., From ft. to ft., From 4 ft. to 24 ft.								
What is the nearest source of possible contamination:								
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? West How many feet? 10 ft. plus								
Direction none	ITHOLOGIC L	OG	From	То	1104 1101		GIC LOG	
0 3 topsoil								
3 25 fine sand								
25 36 medium sand								
				L				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and								
was completed on (mo/day/year) 6/28/19 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/1/19								
under the business name of Harp Well and Pump Service by (signature)  Todd S. Horp								