	WATER WEL	L RECORD F	orm WW	C-5 KS	SA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION		SECTI	ON NUMBER	TOWNSHIP		RANGE NUM	
Sedgwick		NE 1/4 NE	1/4	2	T 27	S	R 1W	E/W
Distance and direction from nearest town or 1/8 Mile West of West St.			Kancac		(4 const	ruct on 1 p	ermit)	
	ICHITA, CITY O		ixansas		(4 cons	ruct on 1 p	or mit,	
	5 N. Main					Board of Agric	culture, Division of Water	er Resource
CITY, STATE: W	ichita, Kansas			CODE: 67	202	Application Num	ber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLET	TED WELL: 35	ft.		ELEVATION:			
N N	Depth of groundwater En		ft.			ft.	=10.411	ft.
	WELL'S STATIC WATER			V LAND SU	RFACE MEASU			
	Pump t Est, Yield:	test data: Well wate gpm Well wate			ft. after ft. after		of pumping @ of pumping @	gpn
M M E	Bore Hole Diameter	12 in.	to 3	5 ft.	and	in.	to	ft.
-	WELL WATER TO BE U	JSED AS:				9. Dewaterin	ng 11. Injection	on well
SW SE-	1. Domestic 3. Fee				nd garden only	10. Monitorin	12. Other (Spec	ify below
S		iustrial 6. Oil field wa gical sample submitted to D		8. Air con	NO		v <u>hat mo</u> /day/yr was	sample
5	submitted	great sample subtritted to b	oparanont:		ater Well Disinfe	ected?	YES NO	,
5 TYPE OF CASING USED:	5. Wrought Iron	n 7. Fiberglass	9. Oth	ner (Specify	below) CAS	ING JOINTS:	Glued T	hreaded
1. Steel 3. RPM	(SR) 6. Asbestos-Ce		SDR	2-26			Welded C	Clamped
2. PVC 4. ABS Blank casing diameter 8	in. to 20		in,	to	ft.,	Dia. i	in. to	ft.
	12 in.,	,			,			16.
Casing height above land surface: TYPE OF SCREEN OR PERFORAT	,	Weight:	3.32 10	s. / ft.	wan un	ckness or gaug	ge No332	
Steel 3. Stainless Steel		7. PVC	9. AE	3S	11. Oth	ner (specify)		
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. As	sbestos-Cen	nent 12. No	ne used (open	hole)	
SCREEN OR PERFORATION OPEN	NINGS ARE:							
1. Continuous slot 3. Mi	Il slot 5. Gau	uzed wrapped	7. Tor	ch cut	9. Drill	ed holes	11. None (ope	en hole)
2. Louvered shutter 4. Ke	y punched 6. Wire	e wrapped	8. Sav	v cut	10. Othe	er (specify)		
SCREEN - PERFORATION INTERV	AL From	20 ft. to	30	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS	S: From	20 ft. to	35	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. N	eat cement	2. Cement Grout	3	Bentonite		Other bent	onite hole plug	5
Grout Intervals: From	ft. to	ft., From	ft.	to	ft.,	From 0	ft. to 2	0 ft.
What is the nearest source of possible 1. Septic tank 4. Lat	teral lines 7. Pi	it privy 1	0. Livestoc	k pens	13. Insecti	cide storage	15. Oil well/Ga	s well
			1. Fuel storage		14. Abandon water well 16. Other (specify below			
3. Watertight sewer line 6. Se	epage pit 9. Fe	eed yard 1	2. Fertilizer	storage			None App	arent
Direction from well?			1 =		How ma	any feet?	010100	
From To	LITHOLOGIC L	LOG	From	То		LITHOLC	OGIC LOG	
0 3 topsoil 3 21 fine sand								
21 35 medium sa	and							
								-
7					1 05 5	plugged	under my juriodictic	n and
7 Contractor's or Landowner's C				constructed		plugged	under my jurisdictio	ii ailu
was completed on (mo/day/year)	7/24/19				knowledge and		20/10	
Kansas Water Well Contractor's L	icense No. 236	This water w	ell record wa	is completed	d on (mo/day/yea	,	29/19	
under the business name of Ha	rp Well and Pump	Service	by (si	gnature)	T	odd S	. Harp	