		WATE	R WELL REC	ORD F	orm W	WC-5 I	KSA 82a-	1212			
1.5.1	TION OF WA	1			SE	CTION NUMBI	ER TOWN	SHIP NUMBER	RANG	E NUMBER	
	lgwick	NE NE	1/4 NW 1/		1/4	32	<u> </u>	27 S	R	1W E/W	
1	22 W. E	rom nearest town or city street address thner Wichita, Kan		city							
	ATER WELI						_				
	ST. ADDRES	S,BOX #: 10022 W. Est	iner					Board of Ag	griculture, Division	of Water Resource	
	CIT	, STATE: Wichita, Kans	sas			ZIP CODE:	67209	Application Nu	ımber:		
	ATE WELL'S	OCATION 4 DEPTH OF C	COMPLETED WELL	.: 12	0 ft		ELEVATIO	N:			
	1 414 7 114 3	Depth of ground	lwater Encountered:			ft.		ft.		ft.	
	X	WELL'S STATI	C WATER LEVEL	27	FT. BEL	OW LAND S	URFACE MEA	ASURED ON mo	/day/yr: 9/	26/19	
1' +	NM	NE	Pump test data:	Well water	er was		ft. after	hour	s of pumping @	gpn	
w Wije		Est. Yield:	gpm meter 12	Well water		120	ft. after		s of pumping @		
<u>₹</u> "[10	E Bore Hole Dia	TO BE USED AS:	in.	to	120 ft	t. and	in.	to	ft.	
1. 1	sw	1. Domestic		. Public wat	er supply	7. Lawn	and garden o	9. Dewater	···a	ijection well (Specify below)	
$\Pi \Pi$	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
-	S	Was a chemical submitted	bacteriological sample	submitted to De	epartment?		NO Water Well Dis		what mo/day/yi	,	
5 T	YPE OF CA	SING LISED:							YES	NO	
틴 .	1. Steel	3. RPM (SR) 5. Wro	ught Iron 7.	Fiberglass		Other (Specify	y below) C	ASING JOINTS:	Glued Welded	Threaded	
	2. PVC	4. ABS 6. Asb	estos-Cement 8.	Concrete tile	e SD	R-26			weided	Clamped	
Blank ca	asing diame	er 5 in. to	100 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing	Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE O		OR PERFORATION MATERIAL:		_					•		
	1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
		PRATION OPENINGS ARE:									
	tinuous slo		5. Gauzed wrappe	ed		orch cut	9. D i	rilled holes	11. None (open hole)	
2. Lou	vered shutt	4. Key punched	6. Wire wrapped		(8. Sa	aw cut	10. O	ther (specify)			
SCREEN	- PERFOR	TION INTERVAL From	100 ft.	to	120	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
	GRAVEL PA	CK INTERVALS: From	24 ft.	to	120	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
6 GRO	UT MATER	ALS: 1. Neat cement	2. Cement G	Frout	;	3. Bentonite		Other bent	onite hole p	lug	
Grout Intervals: From ft. to ft., From 4 ft. to 24 ft., From 94 ft. to 96 ft.											
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well											
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)											
	rtight sewe		9. Feed yard	12.	. Fertilize	r storage					
	from well?	North				Ü	How r	nany feet? 50 f	t. plus		
From	То	LITHOLO	GIC LOG		From	То		LITHOLO			
0	3	topsoil									
<u>3</u>	51	clay fine sand									
51	96	clav									
96	120	medium sand									
				-							
		Nr.									
Cont	ractor's or L	ndowner's Certification: This wa	ter well was 1. Co	nstructed	2. rec	onstructed	or 3.	plugged ur	nder my jurisdict	ion and	
_		no/day/year) 9/26/19					nowledge and				
		Contractor's License No. 236				•	on (mo/day/ye		/10		
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp											