1 LOCATION OF V	VATER WELL:		WATER	· VV LLL	, LO		i Oilli		ION NUMBE	SA 82a-	SHIP NUMBE	R I	RANGE N	NUMBER
Sedgwick				1/4 NI	E 1/	4 NW	7 1/4		2	Т	27 s		R 1V	
stance and direction		town or city str										-		
2818 N. Ai		CILAD		chita, K	ansas									
RR#,ST. ADDR	ELL OWNER:		P HOM N. Collec		# A						Board	d of Agricultur	e, Division of \	Water Resourc
	ITY, STATE:		ta, Kans		TA.			715	CODE: 6	7206	Applicat	tion Number:		
LOCATE WELL			EPTH OF C) WELI		50	ft.	0000	ELEVATIO				
WITH AN "X" IN	N SECTION BO	x: -	n of ground					ft.			ft.			ft.
	X	WEL	L'S STATIO	C WATER L	.EVEL	14	FT. I	BELO\	N LAND SI	JRFACE ME	ASURED OF	N mo/day/y	r: 5/7	7/20
I NW	NE			Pump tes	t data:	Well v	vater was	;		ft. after		hours of p	umping @	gp
w	,	1 1	Est. Yield:		om 12		water was		•	ft. after	•	hours of p	umping @	gp
≦ w	1		e Hole Diar L WATER		12	in.		to 5	U ft	. and		in.	to	ft
sw	sE		Domestic	3. Feedl		5. Public v	water su	oply ⁴	7. Lawn	and garden	only 9. De	watering	-	ection well Specify belo
		2.1	rrigation	4. Indus					8. Air co		10. M c	nitoring w	ell	•
· <u> </u>	S		s a chemical/	bacteriologica	al sample	submitted t	o Departm	ent?	YES	NO	_		_	was sample
TYPE OF	CASING USE		nitted							Water Well D		YES		NO
1. Steel		. RPM (SR)	5. Wro	ought Iron	7	7. Fiberglas	ss	9. Ot	her (Specif	y below)	CASING JOI	_	lded	Threaded
2. PVC	\rightarrow	. ABS	6. Asb	estos-Cem	ent 8	3. Concrete	e tile	SDF	R-26			we	ided	Clamped
Blank casing dia	ımeter	5 in	ı. to	40	ft.,	Dia.		in.	to	ft.,	Dia.	in.	to	ft.
Casing height a	bove land sur	face:	12 ir	٦.,		Weight:	2.35	lb	s. / ft.	Wa	III thickness	or gauge No	. .21 4	į.
YPE OF SCRE														
Steel Brass	3. Stainle:		5. Fiberg			PVC >		9. AE			. Other (spec	• •		
	4. Galvan		6. Concr	ete i lie	8.	. RMP (SR	.)	10. As	bestos-Ce	ment 12	. None used	(open noie)	,	
SCREEN OR PE 1. Continuous		OPENINGS 3. Mill slot		5 Causa	d			7 T	-h	0.1	Duillad balas		44 Nome /	aman hala)
				5. Gauze					ch cut		Drilled holes		11. None (open hole)
2. Louvered st		4. Key pun	iched	6. Wire w	• • •	ı		8. Sav	v cut	10.	Other (spec	ify)		
CREEN - PERF	ORATION IN	TERVAL	From	40) ft.		to £	50	ft.,	From	ft.		to	ft.
			From		ft.		to		ft.,	From	ft.		to	ft.
GRAVEL	L PACK INTE	RVALS:	From	24	ft.		to 5	50	ft.,	From	ft.		to	ft.
T			From		ft.		to		ft.,	From	ft.		to	ft.
GROUT MA		1. Neat ce			Cement	Grout		3	Bentonite	•	Other	bentonit	te hole pl	
Grout Interval hat is the neare		ossible cont	ft. tamination:	to	ft.,	From	ı	ft.	to	ft.,	From	1 4 f	t. to	. 24 ft
1. Septic tank		4. Lateral li		7. Pit pi	rivy		10. Liv e	stock	pens	13. Ins	ecticide sto	rage 1	5. Oil well/	Gas well
2. Sewer lines	i	5. Cess Po	ol	8. Sewa	ige lage	oon	11. Fue	l stor	age	14. Ab	andon wate	r well 1		pecify below
3. Watertight s		6. Seepage	pit	9. Feed	yard		12. Fer	tilizer	storage				None	e Yet
Direction from w		West	T. 101 0						<u>-</u>	Hov	many feet?			
From To			<u>ITHOLO</u>	GIC LO	<u>G</u>		Fro	om	То		LITH	<u>IOLOGI</u>	C LOG	
$\begin{array}{c cccc} 0 & 3 \\ 3 & 12 \end{array}$		ш					+	_						
12 27		and												
27 50		ım sand												
				· · · · · ·										
							+							
1														
														
	-													
		· · · · · · · · · · · · · · · · · · ·				·- · · · · · · · · · · · · · · · · · ·	+	-						,
		· · · · · · · · · · · · · · · · · · ·			-									

was completed on (mo/day/year) 5/7/2020 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/11/2020 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp