		WATERW	ELL REC	JORD F	orm vv v	VC-5 R	SA 82a-12	12		
1 LOCATION OF WATE	R WELL:	FRACTION			2555	TION NUMBE	0.30	IP NUMBER	RANGE N	
Sedgwick		NW 1/4		1/4 NE	1/4	14	T 2	.7 s	R 1V	N E/W
Distance and direction fro			Il if located with	nin city?						
4306 W. 12th		hita, Kansas								
2 WATER WELL		RLEE, Gary W. 12th N.						Board of Agri-	culture, Division of \	Water Resource
RR#,ST. ADDRESS		w. 12th N. iita, Kansas			_	IP CODE: 6	7212	A U 4U AU		
			N FTED 1415	LL: 50		IP CODE: V		Application Num	nder:	
3 LOCATE WELL'S LE WITH AN "X" IN SE	CTION BOX:	DEPTH OF COMP					ELEVATION:			
N		oth of groundwate			ft			ft.		ft.
	X WE	ELL'S STATIC WA	ATER LEVEL			OW LAND S	URFACE MEAS	URED ON mo/d	lay/yr: 6/1	./20
NW -	NE		mp test data				ft. after		of pumping @	gpm
w W		Est. Yield:	gpm r 12	Well was		5 0 -	ft. after		of pumping @	gpm
 	1 1	ore Hole Diamete ELL WATER TO E	-	in.	to .	50 ft	. and	in.	to	ft.
sw	0.5		Feedlot		ter supply	7. Lawn	and garden on	9. Dewaterii	.8	ection well
			Industrial	6. Oil field w				10. Monitorin		pecify below
S		/as a chemical/bacte				YES	NO		vhat mo/day/yr	130
		bmitted				Was	Water Well Disi	nfected?	YES	NO
5 TYPE OF CAS		5. Wrought	t Iron	7. Fiberglass		ther (Specif		SING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SF	6. Asbesto	s-Coment	8. Concrete ti	5P	R - 26	•		Welded	Clamped
2. PVC	> 4. ABS				-					
Blank casing diamet	er 5	in. to	30 ft.,	Dia.	in.	to	ft.,	Dia. i	in. to	ft.
Casing height above		12 in.,		Weight:	2.35 I	bs. / ft.	Wall t	hickness or gaug	je No214	ļ
TYPE OF SCREEN				7 01/0			44.0			
	3. Stainless Steel	5. Fiberglass	_	7. PVC	9. A			ther (specify)		
	4. Galvanized	6. Concrete 1	Tile	8. RMP (SR)	10. A	\sbestos-Ce	ment 12. N	one used (open	hole)	
SCREEN OR PERFO										
1. Continuous slot 3. Mill slot 5. Gauzed wrapped						7. Torch cut 9. Drilled hole			11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)										
SCREEN - PERFORA	ATION INTERVAL	From	30 f	t. to	50	ft.,	From	ft.	to	ft.
		From	f	t. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From			24 ff	. to	50	ft.,	From	ft.	to	ft.
	,,	From	fi							
O COOLE MATER	IALC:					ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									_	
Grout Intervals: What is the nearest s	From ource of possible co	ft. to	ft.	, From	ft.	to	ft.,	From 4	ft. to	24 ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								Gas well		
2. Sewer lines	5. Cess P	ool 8	. Sewage la	goon 1	1. Fuel sto	rage	14. Aban	don water well	16. Other (s	pecify below)
3. Watertight sew			. Feed yard	- 1	2. Fertilize	r storage				
Direction from well?	North	go pit	,				How m	nany feet? 20 f	t. plus	
From To	1	LITHOLOGIC	CLOG		From	То	1	LITHOLO		
0 3	topsoil									
3 25	fine sand									
25 50	medium sand									
	 				1					
	 				-					
									-	
						<u> </u>				
								A 1500		
					<u> </u>	<u> </u>				
	-									
		•			 	<u> </u>	<u> </u>			
7 Contractor's or	J. Condense de C. 100		0					-1		··
	Landowner's Certific		well was 1.0	constructed	ノ 2. re	constructe	d or 3.	plugged (under my jurisdic	tion and
was completed on	(mo/day/year)	6/1/2020	а	nd this record i	s true to the	e best of my	knowledge and	belief.		
Kansas Water Wel	l Contractor's Licens	se No. 236		This water we	Il record wa	as completed	d on (mo/day/ye	ar) 6/3/3	2020	
under the business	name of Harp	Well and Pur	np Servic	e	by (si	gnature)	$\boldsymbol{ au}$	odd S	Ham	
1	P		t- ~ or . 10	-	· , (-:	,	- 1	Jun 3	. TWI	,