KSA 82a-1212 WATER WELL RECORD Form WWC-5 1 LOCATION OF WATER WELL: RANGE NUMBER SECTION NUMBER TOWNSHIP NUMBER FRACTION SE 30 27 1W E/W Sedgwick NE NE Т S R 1/4 Distance and direction from nearest town or city street address of well if located within city? 10407 W. Hayden Ct. Wichita, Kansas LAUBER, Josh WATER WELL OWNER: Board of Agriculture, Division of Water Resource 10407 W. Hayden Ct. RR#,ST. ADDRESS,BOX #: ZIP CODE: 67209 Wichita, Kansas Application Number: CITY, STATE 120 ELEVATION: 4 DEPTH OF COMPLETED WELL LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft ft. Depth of groundwater Encountered: 20 9/8/20 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: gpm Pump test data: Well water was ft. after hours of pumping @ -N₩ NE hours of pumping @ gpm Well water was ft. after Est. Yield: gpm 12 ft. 120 Σ Bore Hole Diameter and in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; if yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? YES (NO Was Water Well Disinfected? submitted (YES) NO TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 10δ Blank casing diameter 5 Dia. in. Dia ft. to 12 2.35 Casing height above land surface: in. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 3. Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized Concrete Tile Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 11. None (open hole) 9. Drilled holes 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 100 120 From to ft.. From ft. ft. tn From ft., From ft. ft. to 24 120 GRAVEL PACK INTERVALS: ft. to From ft., From ft. to ft. ft. ft From to From ft. to ft. 6 **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: ft 24 From ft.. From to ft.. From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit East How many feet? 60 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From From Τо lο 0 topsoil 26 clay 26 42 fine sand 42 91 clay 91 95 fine sand 95 120 medium sand under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1 constructed 2 reconstructed plugged 9/8/2020 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 9/10/2020 Kansas Water Well Contractor's License No. 236 Todd S. Harp under the business name of Harp Well and Pump Service by (signature)