		WATER W	ELL REC	CORD I	orm W	NC-5 K	SA 82a-1	212		
1 LOCATION OF WAT	ER WELL:	FRACTION			SEC	TION NUMBE	R TOWNS	HIP NUMBER	1 -	NUMBER
Sedgwick		NW 1/4		1/4 SW	1/4	31	Т	27 S	RI	W E/W
Distance and direction from 3347 N. Judi	•	Wichita, Ka		nin city?						
2 WATER WELL		RP HOMES	111343							
RR#,ST. ADDRESS		N. Collective	Ste#A					Board of Ag	nculture, Division of	Water Resource
CITY	, STATE: Wich	ita, Kansas			z	IP CODE: 6	7206	Application Nu	mber:	
3 LOCATE WELL'S L	OCATION 4	DEPTH OF COMP	LETED WE	LL: 7	0 ft.		ELEVATION	:		
WITH AN "X" IN SE		oth of groundwater	r Encountere	ed:	fi	t.		ft.		ft.
!	WE	ELL'S STATIC WA	ATER LEVEL	. 31	FT. BELC	OW LAND SU	JRFACE MEA	SURED ON mo	/day/yr: 8 /1	12/20
' NW	NE		mp test data				ft. after		s of pumping @	gpm
w Z		Est. Yield: ore Hole Diameter	gpm 12	Well wa	iter was to	70 "	ft. after		rs of pumping @	gpm
= " X	, i I	ELL WATER TO B			το	70 ft.	and	in.	to u 11 Ini	ft. jection well
sw	d-		Feedlot		ter supply	7. Lawn	nd garden o	9. Dewater	9	Specify below)
		-	Industrial	6. Oil field v				10. Monitori	-	
s		/as a chemical/bacter bmitted	riological samp	ole submitted to	Department?	YES Was V	NO Vater Well Dis	· -	what mo/day/yr	was sample NO
5 TYPE OF CA	SING USED:	E Mrought	Iron	7 Fiboralese	9.0	Other (Specify		ASING JOINTS:	Glued	Threaded
1. Steel	3. RPM (SR	•		7. Fiberglass	S.D.	R-26	20.0,		Welded	Clamped
2. PVC	> 4. ABS	6. Asbestos		8. Concrete t	ile 5D	10-20				
Blank casing diamet	ter 5		50 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above		12 in.,		Weight:	2.35	lbs. / ft.	Wall	thickness or gau	ige No21	4
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFO	ORATION OPENING	S ARF		, ,	,				,	
1. Continuous slo			Gauzed wra	pped	7. T c	orch cut	9. D i	rilled holes	11. None ((open hole)
2. Louvered shutte	er 4. Key pu		Nire wrappe	• •	(8.5a	aw cut	10. 0	ther (specify)	,	
SCREEN - PERFORA	• •							, , , , ,		
SCREEN - PERFOR	ATION INTERVAL	From	50 ft			ft.,	From	ft.	to	ft.
GRAVEL PA	ACK INTERVALS:	From	24 ft			ft.,	From	ft.	to .	ft.
O O O O O O O O O O O O O O O O O O O	ON INVENVALO.	From From	£-7 it			ft.,	From	ft.	to	ft.
6 GROUT MATER	IAI S:					ft.,	From	ft.	to	ft.
Grout Intervals:	IALS: 1. Neat o	ement ft. to	2. Cemer ft.			3. Bentonite			tonite hole p	24
What is the nearest s		ntamination:			ft.		ft.,	From 4	ft. to	o 24 ft.
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Ga										
2. Sewer lines	5. Cess P	ool 8.	Sewage la	_	11. Fuel sto	•	14. Abai	ndon water well	16. Other (s	specify below)
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North How many feet? 10 ft. plus										
From To		ITHOLOGIC	CLOG		From	То	How	many feet? 10	OGIC LOG	
0 3	topsoil		200		1 10111	 '`		LITTIOL	JOIO LOG	
3 31	clay				ļ					
31 41	fine sand				<u> </u>					
41 47 47 70	clay medium sand									
						<u> </u>				
	 							······································		· ····
					-	-				
7 Contractor's or	Landowner's Certific	ation: This water	well was 1 (Constructor) 2, re	constructed	or 3.	plugged	under my jurisdic	ction and
was completed on		8/12/2020		nd this record				,		
1			ar			•	•		1/2020	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/14/2020										
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb)