		WATER W	ELL RE	CORD	Form V	WC-5	KSA 82a-1	212			
1 LOCATION OF WATE	R WELL:	FRACTION	O.F.			SECTION NUMB		SHIP NUMBER		GE NUM	
Sedgwick		NW 1/4		1/4 NE	1/4	11	T	27 s	R	1W	EAW
Distance and direction from 4215 W. Bella	•	Wichita		itmin city?	•				:		
2 WATER WELL C		Z, Edward	Kansas ,								
RR#,ST. ADDRESS		5 W. Bella Vis	sta					Board of A	griculture, Divisio	on of Wate	er Resource
		hita, Kansas				ZIP CODE:	67212	Application N	umber:		
3 LOCATE WELL'S LO	CATION 4	DEPTH OF COM	PLETED W	ELL:	40	ft.	ELEVATIO	N:			
WITH AN "X" IN SEC	De	epth of groundwate	er Encounte	red:		ft.		ft.			ft.
	W	ELL'S STATIC W	ATER LEVE	EL 15	FT. B	ELOW LAND S	SURFACE ME	ASURED ON mo	o/day/yr:	9/14/2	:0
NW	NE-1	Pu	ımp test da	ta: Well v	ater was		ft. after	hou	ırs of pumping	@	gpm
w Wile	' ^L L	Est. Yield:	gpm		vater was	. 40	ft. after		urs of pumping	•	gpm
≥ w		Bore Hole Diamete ÆLL WATER TO E			t	0 40	ft. and	in.	•	to Injecti	ft.
9w			. Feedlot		vater sup	ply 7 Lawr	and garden	9. Dewate	,g	. injecti er (Sne	cify below)
		2. Irrigation 4	. Industrial	6. Oil field	water su	pply 8. Air c	onditioning	10. Monito	ring well		
		Was a chemical/bacte	eriological sa	mple submitted t	o Departme		NO		yES	y/yr was NO	•
7/05/05/04/		ubmitted	•				Water Well D		$\succ$		<del> </del>
5 TYPE OF CAS	SING USED: 3. RPM (S	(R) 5. Wrough	t Iron	7. Fibergla:	~	9. Other (Spec	ify below)	CASING JOINTS	: Glued Welded	•	hreaded
2. PVC	> 4. ABS	6i Asbesto	s-Cement	8. Concrete	tile :	SDR-26			a A GOOGO	•	Clamped
Blank casing diameter	_	in. to	30 ft.,	, Dia.	, i	n. to	ft.,	Dia.	in. to	0	ft.
Casing height above	e land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wa	III thickness or ga	uge No	214	
TYPE OF SCREEN						•					
1. Steel	8. Stainless Steel	<ol><li>Fiberglass</li></ol>	. <	7. PVC		9. ABS	11	. Other (specify)			
2. Brass 4	I. Galvanized	6. Concrete	Tile	8. RMP (SR	) 1	0. Asbestos-C	ement 12	None used (ope	en hole)		
SCREEN OR PERFO	RATION OPENIN	GS ARE:									
1. Continuous slot	3. Mill s	<b>lot</b> 5.	Gauzed w	rapped	7	. Torch cut	<b>9</b> . l	Drilled holes	11. No	ne ( ope	en hole)
2. Louvered shutte	er 4. Key p	ounched 6.	Wire wrap	ped	Ç	3. Saw cut	10.	Other (specify)			
SCREEN - PERFORA	ATION INTERVAL	From	30	ft.	to 4	0 ft.,	From	ft.	to	<b>5</b>	ft.
		From		ft.	to	ft.,	From	ft.	to	5	ft.
GRAVEL PA	CK INTERVALS:	From	24	ft.	to 4	O ft.,	From	ft.	to	<b>o</b>	ft.
		From		ft.	to	ft.,	From	ft.	to	5	ft.
6 GROUT MATER	IALS: 1 Nest	cement	2. Cem	ent Grout		3. Bentoni	Ite	Other be	ntonite hol	e plug	
Grout Intervals:	From	ft. to		ft., From	1	ft. to			4 ft.	to 2	•
What is the nearest se			7. Pit privy		10. Live	stock pens	13 ine	ecticide storage	15. Oil v	well/Gas	r well
1. Septic tank	4. Latera	ai iiii <del>es</del>	B. Sewage			storage		andon water we	40 046		ify below)
2. Sewer lines	5. <b>Cess</b>		_			ilizer storage	14. AU	andon water we	41		,
3. Watertight sewe	South	age pit	9. <b>Feed ya</b> r	u	12. FeIt	iiitai smiaga	Hov	w many feet? 10	) ft. nlus		
From To	Journ	LITHOLOGI	CLOG		Fro	m To	T		OGIC LO	G	
0 3	topsoil		0 100								
3 15	clay										
15 24	fine sand				+						-
24 40	medium san	d			<del></del>		<del> </del>				
	<del> </del>								·		
·	<del> </del>				+-						
	1										
1 11											
	<del> </del>				-		1				
7	<u> </u>				_			-1		d = d1 = 11	
	Landowner's Certif					reconstruct		plugged	under my ju	nsdiction	n and
was completed on	(mo/day/year)	9/14/2020	,	and this reco	rd is true t	to the best of m	ny knowledge a	and belief.			
Kansas Water Wel	l Contractor's Licer	nse No. 236		This water	well recor	d was complet	ed on (mo/day	/year) 9/1	16/2020		
under the business	name of Harp	Well and Pu	mp Serv	ice	b	y (signature)		Todd	S. Ha	rb	