WATER WELL RECO	RD Form WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBE		RANGE NUMBER
Sedgwick NE 1/4 SW 1/4	SE 1/4 24	T 27 S	R 1W E/W
Distance and direction from nearest town or city street address of well if located within ci	?		
149 S. Mt. Carmel Wichita, Kansas			
DAVIS, Ray J.		Board of Agri	culture, Division of Water Resource
RR#,ST. ADDRESS,BOX #: 149 S. Mt. Carmel CITY, STATE: Wichita, Kansas	ZIP CODE: 6	(7213 Application No.	
	40		nder:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL:	1.	ELEVATION:	
N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL		URFACE MEASURED ON mo/o	
Pump test data:	Well water was		s of pumping @ gpm
Est. Yield: gpm  E Bore Hole Diameter 12 i	Well water was		s of pumping @ gpm
	. to <b>40</b> fi		to ft.
WELL WATER TO BE USED AS:  1. Domestic 3. Feedlot 5.	Public water supply 7. Lawn	and garden only	•
		nditioning 10. Monitoria	12. Other (Specify below)
S Was a chemical/bacteriological sample s	······································		what mo/day/yr was sample
submitted		Water Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7.	iberglass 9. Other (Specif	y below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR)	SDD 26	•	Welded Clamped
4. ADO	Concrete tile SDR-20		
Blank casing diameter 5 in. to 30 ft.,	Dia. in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., w	eight: 2.35 lbs. / ft.	Wall thickness or gaug	ge No. 214
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1. Steel 3. Stainless Steel 5. Fiberglass 7. F	/C 9. ABS	<ol><li>Other (specify)</li></ol>	
2. Brass 4. Galvanized 6. Concrete Tile 8. F	MP (SR) 10. Asbestos-Ce	ment 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrappe	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
	to 40 ft		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	10 14,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft.	to $40$ ft.,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement 6	rout 3. Bentonit	e Other bent	tonite hole plug
Grout Intervals: From ft. to ft.,	From ft. to	ft., From 4	ft. to <b>24</b> ft.
What is the nearest source of possible contamination:  1 Septic tank 4 Lateral lines 7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
46 Other Innesis, helevy			
2. Sewer lines 5. Cess Fooi 14. Abandon water wen			
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well? South	12. Fertilizer storage	How many feet? 15	ft nluc
From To LITHOLOGIC LOG	From To		
0 3 topsoil	FIOIII 10	LITHOLO	OGIC LOG
3 12 clay			
12 20 fine sand			
20 40 medium sand			
Contractor's or Landowner's Certification: This water well was 1	nstructed 2. reconstructe	ed or 3, plugged	under my jurisdiction and
2/1/2021	nstructed 2. reconstructer		under my jurisdiction and
was completed on (mo/day/year) 2/1/2021 and	nis record is true to the best of my	/ knowledge and belief.	
was completed on (mo/day/year) 2/1/2021 and		/ knowledge and belief.	/2021