

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

[]

Well ID

[]

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Sedgwick Fraction NE 1/4 SW 1/4 SW 1/4 NW 1/4 Section Number 2 Township Number T 27 S Range Number R 1 E W

2 WELL OWNER: Last Name: Business: J Russell Communities Address: P.O. Box 75337 City: Wichita State: KS ZIP: 67275 Street or Rural Address where well is located Reserve F Sandcrest 3rd Addition, from W 26th St N & N Curtis St go East 260 ft and N 40 ft

3 LOCATE WELL WITH 'X' IN SECTION BOX: N W E S

4 DEPTH OF COMPLETED WELL: 40 ft. Depth(s) Groundwater Encountered: 1) 13 ft. 2) ft. 3) ft. or 4) Dry Well WELL'S STATIC WATER LEVEL: 10 ft. below land surface, measured on (mo-day-yr) 07/22/2021

5 Latitude: 37.732070 Longitude: -97.405690 Datum: WGS 84 Source for Latitude/Longitude: GPS (unit make/model):

6 Elevation: ft. Source: Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 2. Public Water Supply: well ID Dewatering: how many wells? Aquifer Recharge: well ID Monitoring: well ID Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Injection Oil Field Water Supply: lease Test Hole: well ID Cased Uncased Geotechnical Geothermal: how many bores? Closed Loop Horizontal Vertical Open Loop Surface Discharge Inj. of Water Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 7.8 in. to 40 ft. Diameter in. to ft. Diameter in. to ft. Casing height above land surface 16 in. Weight lbs./ft. Wall thickness or gauge No. SDR-26

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft. GRAVEL PACK INTERVALS: From 22 ft. to 40 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 3 ft. to 22 ft. From ft. to ft. From ft. to ft. From ft. to ft.

Nearest source of possible contamination: No potential source of contamination within 200 ft. Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify): Direction from well? South Distance from well? 100 ft.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-2 Top Soil, 2-7 Clay, 7-13 Sandy Clay, 13-22 Medium Sand, 22-40 Small Gravel. Includes Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 07/22/2021 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 884. This Water Well Record was completed on (mo-day-year) 09/19/2021 under the business name of Weninger Drilling, LLC