		ECORD		WWC-5			ion of Water			
				e in Well Use			irces App. No		Well ID	
-		ATER WELL	:	Fraction			on Number	Township Nun		
	Sedgwic			NW ^{1/4} NE ^{1/4} SE		1			S R1 E W	
	OWNER: 1	ast Name: HAGO	GAR	First: Virginia				ere well is located		
Business: Address: 2389 N. Richmond Ave.									er's address, check here:	
Address:										
City: Wichia State: Kansas ZIP: 67204										
-	4 DEPTH OF COMPLETED WELL: 40						ft. 5 Latitude: 37.72636			
	WITH A IN D. d. (c) Council and a function for a subscription of (1)						· · ·			
	(2) (2)						Horizontal Datum: WGS 84 🗆 NAD 83 🗆 NAD 27			
r	WELL'S STATIC WATER LEVEL: 14						Source for Latitude/Longitude:			
	below land surface, measured on (mo-day-yr).									
NW	NWNE above land surface, measured on (mo-day-yr)							(WAAS enabled?		
	Pump test data: Well water was ft. after hours pumping gpm						□ Land Survey □ Topographic Map			
W	E	vater was				line Mapper:				
SW	SE	after	r hours pumping gpm							
			Estimated Yield:gpm				6 Elevation:ft. Ground Level TOC			
5	5	Bore Hole D	Bore Hole Diameter: 12 in. to 40 ft. a				Source: 🗌 Land Survey 🔳 GPS 🗌 Topographic Map			
1 r				in. to	ft			U Other		
7 WELL WATER TO BE USED AS:										
1. Domestic:				ter Supply: well ID					lease	
	Household 6. Dewatering: how many wells?									
	Lawn & Garden 7. Aquifer Recharge: well ID Livestock 8. Monitoring: well ID									
	□ Livestock 8. □ Monitoring: well 1D									
3. 🗌 Feedlo							b) Open Loop 🗌 Surface Discharge 🗌 Inj. of Water			
4. 🗌 Industr	rial		Recovery							
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:										
Water well disinfected? Myes \Box No										
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded										
Casing diameter in. to										
Casing height above land surface12 in. Weight 2.,35 lbs./ft. Wall thickness or gauge No. SDR-26										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
□ Steel □ Stainless Steel □ Fiberglass ■ PVC □ Other (Specify)										
Brass Galvanized Steel Concrete tile None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify)										
SCREEN-PERFORATED INTERVALS: From 30 ft. to 49 ft., From ft., From ft. to ft.										
GRAVEL PACK INTERVALS: From 24 ft. to 49 ft., From ft. to ft. to ft.										
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other										
Grout Intervals: From										
Nearest source of possible contamination:										
Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage										
□ Sewer Lines □ Cess Pool □ Sewage Lagoon □ Fuel Storage □ Abandoned Water Well										
Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Other (Specify) Other (Specify) Other (Specify)										
Direction from well? West										
10 FROM	TO		ITHOLO		FRO				or PLUGGING INTERVALS	
0		topsoil			FRO	IVI	10			
3		clay								
8		fine sand							•	
20	40	medium sam	nd							
	Notes:									
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗷 constructed, 🗌 reconstructed, or 🗌 plugged										
under my jurisdiction and was completed on (mo-day-year) 97./27./29.22. and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No										
Mail 1 v	white copy alon	g with a fee of \$5	5.00 for each	constructed well to: Ka	nsas Departr	nent of	Health and En	vironment, Bureau of V	Vater, GWTS Section,	
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.										
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015										