	WATER WELL	RECORD Fo	rm WW0	C-5 KS	SA 82a-1212				
1 LOCATION OF WATER WELL:				ON NUMBER			RANGE NUMBER		
Sedgwick			1/4	2	T 27	s	R 1W	/ E/W	
Distance and direction from nearest tow Emerald Bay, Block 1		, Kansas							
2 WATER WELL OWNER:	EMERALD BAY ES								
RR#,ST. ADDRESS,BOX #:	BOX #: 4900 W. 21st N.					Board of Agriculture, Division of Water Resource			
CITY, STATE:	Wichita, Kansas	<b>,</b>		CODE:		plication Num	ber:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLET	EganeLL: 35	ft.		ELEVATION:	_	•		
N N	Depth of groundwater End		ft.			ft.	. 11/22	ft. 120	
	WELL'S STATIC WATER			LAND SU	RFACE MEASURE ft. after		ay/yr: 11/23 of pumping @	gpm	
0 - NW NE	Est. Yield:	est data: Well wate gpm Well wate			ft. after		of pumping @	gpm	
w Wile	E Bore Hole Diameter	in.	to	ft.	and	in.	to	ft.	
<del>-</del>	WELL WATER TO BE U			7 Lawn a		9. <b>Dewateri</b> r	'9	tion well	
SW SE	1. Domestic 3. Fee			8. Air con	nd garden only	0. <b>Monitori</b> n	12. Other (Sp a well	ecify below)	
	2. Irrigation 4. Indi	ustrial 6. Oil field wa ical sample submitted to De		YES	NO NO		vhat mo/day/yr w		
	submitted			Was V	Vater Well Disinfect	ed?	YES N	10	
TYPE OF CASING USED  1. Steel 3. F	): RPM (SR) 5. Wrought Iron	7. Fiberglass	9. Oth	er (Specify	below) CASING	G JOINTS:	Glued	Threaded	
	ABS 6. Asbestos-Ce	men 8. Concrete tile	е				Welded	Clamped	
Blank casing diameter	16 in. to	ft., Dia.	in.	to	ft., Dia	<b>).</b>	in. to	ft.	
Casing height	ce: 72 in.,	Weight:	lb	s. / ft.	Wall thick	ness or gaug	je No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanize	ed 6. Concrete Tile	8. RMP (SR)	10. As	bestos-Cer	nent 12. None	used (open	nole)		
SCREEN OR PERFORATION C			7 7		9. Drilled	holor	11. None ( d	nen hole)	
		zed wrapped		ch cut			Ti. None (	pen noie,	
2. Louvered shutter 4	1. Key punched 6. Wire	wrapped	8. <b>Sav</b>	v cut	10. Other	(specity)			
SCREEN - PERFORATION INTE	ERVAL From	ft. to		ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTER		ft. to		ft.,	From	ft.	to .	ft.	
a L ODOUT MATERIALS	From	ft. to		ft.,	From	ft. ther	to	ft.	
GROUT MATERIALS:  Grout Intervals: From		2. Cement Grout 26 ft., From	ft.	Bentonite		From	ft. to	ft.	
What is the nearest source of possible contamination:					ft.,				
1. Septic tank 4. Lateral lines				-		13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)			
2. Sewer lines 5. Cess Pool 6. Sewage lagoon 14. Aballuon water well								, , , , , , , , , , , , , , , , , , , ,	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  How many feet?									
From To	LITHOLOGIC L	.OG	From	То			GIC LOG		
				6	compacted so				
<del> </del>			6	26	bentonite hol				
<del></del>	· · · · · · · · · · · · · · · · · · ·	<u> </u>	26	35	chlorinated g	ravel			
			<u> </u>						
				l					
Contractor's of Landowne	r's Certification: This water we	ll was 1. constructed	2. re	constructe	d or 3. pl	ugged	under my jurisdic	tion and	
was completed on (mo/day/y	ear) 11/23/20	and this record	is true to the	best of my	knowledge and be	lief.		•	
Kansas Water Well Contracto	or's License No. 236	This water we	ell record wa	s complete	d on (mo/day/year)	11/	26/20		
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									