

1 LOCATION OF WATER WELL:		Fraction NW 1/4 NW 1/4 NW 1/4		Section Number 9		Township Number 26 17 S		Range Number 1																																											
County: Sedgwick																																																			
Distance and direction from nearest town or city street address of well if located within city? 230' SE of Intersection of 21st Street N and Tyler Rd, Wichita, KS																																																			
01895002 B-3 (MW-1)																																																			
2 WATER WELL OWNER: Groundwater Management Section, Amoco Corporation Amoco No. 3649																																																			
RR#, St. Address, Box # : 4502 East 41st Street Board of Agriculture, Division of Water Resources																																																			
City, State, ZIP Code : Tulsa, OK 74135 Application Number:																																																			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 42 ft. ELEVATION: Approx. Surface Elev.: 1358																																																	
		Depth(s) Groundwater Encountered 1. 35 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 36.6 ft. below land surface measured on mo/day/yr 1/18/89 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 in. to 42 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X																																																	
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 27 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 27 ft. to 42 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24.5 ft. to 42 ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 23 ft. to 24.5 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? West How many feet? 1300																																																			
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>4.5</td><td>Brown to Red-Brown Sandy Lean Clay</td><td></td><td></td><td></td></tr><tr><td>4.5</td><td>11.5</td><td>Red-Brown, Fine to Medium Sand With Silt, Trace Clay</td><td></td><td></td><td></td></tr><tr><td>11.5</td><td>16.0</td><td>Lean to Fat Clay With Variable Sand and Silt Seams</td><td></td><td></td><td></td></tr><tr><td>16.0</td><td>25.5</td><td>Brown and Gray Silty Fine Sand</td><td></td><td></td><td></td></tr><tr><td>25.5</td><td>30</td><td>Red-Brown, Fine to Medium Sand With Interbedded Clayey Zones</td><td></td><td></td><td></td></tr><tr><td>30</td><td>42</td><td>Red-Brown, Fine to Medium Sand With Thin Interbedded Clay Seams and Silt</td><td></td><td></td><td></td></tr></tbody></table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	4.5	Brown to Red-Brown Sandy Lean Clay				4.5	11.5	Red-Brown, Fine to Medium Sand With Silt, Trace Clay				11.5	16.0	Lean to Fat Clay With Variable Sand and Silt Seams				16.0	25.5	Brown and Gray Silty Fine Sand				25.5	30	Red-Brown, Fine to Medium Sand With Interbedded Clayey Zones				30	42	Red-Brown, Fine to Medium Sand With Thin Interbedded Clay Seams and Silt			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																														
0	4.5	Brown to Red-Brown Sandy Lean Clay																																																	
4.5	11.5	Red-Brown, Fine to Medium Sand With Silt, Trace Clay																																																	
11.5	16.0	Lean to Fat Clay With Variable Sand and Silt Seams																																																	
16.0	25.5	Brown and Gray Silty Fine Sand																																																	
25.5	30	Red-Brown, Fine to Medium Sand With Interbedded Clayey Zones																																																	
30	42	Red-Brown, Fine to Medium Sand With Thin Interbedded Clay Seams and Silt																																																	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/17/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. A16 This Water Well Record was completed on (mo/day/yr) 7-6-89 under the business name of Tormac Consultants Inc. by (signature) Douglas D. Albreich																																																			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.																																																			