

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SW NW NW SE

1. Location of well:		County SEDGWICK	Fraction 1/4 NE 1/4 SW 1/4	Section number 1	Township number T 27 S	Range number R 1W E/W																
2. Distance and direction from nearest town or city: Street address of well location if in city: 2506 Cardinal Wichita, Kansas				3. Owner of well: Virgil Thompson R.R. or street: 2506 Cardinal City, state, zip code: Wichita, Kansas																		
4. Locate with "X" in section below: N 1 Mile W <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr></table> E S 1 Mile												Sketch map: N 1 Mile W <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr></table> E S 1 Mile										
5. Type and color of material				From	To	6. Bore hole dia. 11 in. Completion date 5-4-78 Well depth 47 ft.																
S andy Soil				0	2	7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary																
Fine Sand				2	15	8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☒ Lawn ☐ Oil field water ☐ Other																
Fine to Coarse Sand				15	20	9. Casing: Material styrene Height: Above or below/ Threaded ☐ Welded ☒ GI Surface 12 in. RMP ☒ P/C ☐ Weight 47 lbs./ft. Dia. 5 in. to 47 ft. depth Wall Thickness: inches or Dia. 5 in. to 47 ft. depth gage No. 200																
Coarse Sand				20	30	10. Screen: Manufacturer's name Sunflower Plastic Type styrene Dia. 5" Slot 1/4" .06 Length 20' Set between 27 ft. and 47 ft. ft. and 47 ft. Gravel pack? yes Size range of material 1/4-1/8"																
Coarse Sand with Gravel				30	47	11. Static water level: 15 ft. below land surface Date 5-4-78 mo./day/yr.																
						12. Pumping level below land surfaces: ft. after 15 hrs. pumping 15 g.p.m. ft. after 15 hrs. pumping 15 g.p.m. Estimated maximum yield 15 g.p.m.																
						13. Water sample submitted: 15 mo./day/yr. Yes ☐ No ☐ Date 5-4-78																
						14. Well head completion: 12 capped Pitless adapter 12 inches above grade																
						15. Well grouted? yes 1-2 fine sand mix With: 40" Neat cement 14 Bentonite ☒ Concrete Depth: From 40" ft. to 14 ft.																
						16. Nearest source of possible contamination: City ft. 52 Direction East Type Sewer Well disinfected upon completion? ☒ Yes ☐ No																
						17. Pump: ☒ Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other																
(Use a second sheet if needed)																						
18. Elevation:		19. Remarks: Flat Ground																				
Topography: ☐ Hill ☐ Slope ☐ Upland ☐ Valley																						
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Harp Well & Pump 236 Business name Wichita, Kansas License No. _____ Address _____ Signed M. Arnold Date 5-10-78 Authorized representative																						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5