


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>SE</u> 1/4 <u>NW</u> 1/4 <u>SW</u> 1/4	<u>4</u>	<u>T</u> <u>27</u> <u>S</u>	<u>R</u> <u>1W</u> <u>E/W</u>
Distance and direction from nearest town or city street address of well if located within city?					
<u>2406 Ridgeside Circle Wichita, Kansas</u>					
2 WATER WELL OWNER: <u>Hinkle, Gene</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : <u>2406 Ridgeside Circle</u>		Application Number:			
City, State, ZIP Code : <u>Wichita, Kansas</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>65</u> ft. ELEVATION:			
N 1 Mile W E S 		Depth(s) Groundwater Encountered <u>1</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>35</u> ft. below land surface measured on mo/day/yr <u>9-13-91</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>11</u> in. to <u>65</u> ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel		5 Wrought iron	8 Concrete tile	Welded	
2 <u>PVC</u>		3 RMP (SR)	9 Other (specify below)	Threaded	
4 ABS		6 Asbestos-Cement	<u>SDR-26</u>		
5 Fiberglass					
Blank casing diameter <u>5</u> in. to <u>45</u> ft., Dia		in. to ft., Dia			
Casing height above land surface <u>12</u> in., weight <u>2.29</u> lbs./ft. Wall thickness or gauge No. <u>.214</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>7 PVC</u> 10 Asbestos-cement			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped <u>8 Saw cut</u> 11 None (open hole)			
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>45</u> ft. to <u>65</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>24</u> ft. to <u>65</u> ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement	2 <u>Cement grout</u>	3 Bentonite	4 Other
Grout Intervals: From <u>4</u> ft. to <u>24</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? <u>North</u>		How many feet? <u>30</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	19	clay			
19	37	fine sand			
37	65	medium sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-13-91</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>236</u>		This Water Well Record was completed on (mo/day/yr) <u>12-31-91</u>			
under the business name of <u>Harp Well and Pump Service, Inc.</u>		by (signature) <u>Mary Arnold</u>			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4