

1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 SE 1/4 Section Number 4 Township Number T 27 S Range Number R 1 E
 County: Saline
 Distance and direction from nearest town or city street address of well if located within city?
2343 The Time Ct

2 WATER WELL OWNER: Mr. Simpson
 RR#, St. Address, Box #: 2343 The Time Ct
 City, State, ZIP Code: Wichita, Kansas 67205
 Board of Agriculture, Division of Water Resources
 Application Number: none

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: 1300
 Depth(s) Groundwater Encountered 1. 28 ft. 2. 28 ft. 3. 28 ft.
 WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 2-11-99
 Pump test data: Well water was 28 ft. after 28 hours pumping 28 gpm
 Est. Yield 28 gpm: Well water was 28 ft. after 28 hours pumping 28 gpm
 Bore Hole Diameter 9 in. to 28 ft. and 28 in. to 28 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 5 in. to 38 ft., Dia 38 in. to 38 ft., Dia 38 in. to 38 ft.
 Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 16.0
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 16.0
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 48
 SCREEN-PERFORATED INTERVALS: From 38 ft. to 48 ft., From 38 ft. to 48 ft., From 38 ft. to 48 ft.
 GRAVEL PACK INTERVALS: From none ft. to none ft., From none ft. to none ft., From none ft. to none ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 20 ft., From 20 ft. to 20 ft., From 20 ft. to 20 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Top Soil			
8	30	Fine tan sand			
30	48	Coarse tan sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-11-99 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 472 This Water Well Record was completed on (mo/day/yr) 2-11-99
 under the business name of Borden Pump & Well by (signature) David R. Beck