

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction: <u>1/4</u> <u>1/4</u> <u>1/4</u> <u>1/4</u>	Section Number: <u>5</u>	Township Number: T <u>27</u> S	Range Number: R <u>1</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>See Below</u>					
2 WATER WELL OWNER: <u>Jeff Evans</u> RR#, St. Address, Box #: <u>2458 Chadsworth Ct</u> City, State, ZIP Code: <u>Wichita KS 67212</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>61</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 <u>30</u> ft. 2. ft. 3. <u>7-29-92</u> ft.			
		WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm			
Bore Hole Diameter. . in. to . ft., and . in. to . ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes. . No. <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued <u>X</u> Clamped .	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded .	
Blank casing diameter . in. to <u>49</u> ft., Dia . in. to . ft., Dia . in. to . ft.		7 Fiberglass		Threaded .	
Casing height above land surface . <u>12</u> in., weight <u>2.60</u> lbs./ft. Wall thickness or gauge No. <u>160PVC</u>		TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify) .	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify) .			
SCREEN-PERFORATED INTERVALS: From . <u>49</u> ft. to <u>61</u> ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From . <u>23</u> ft. to <u>61</u> ft., From . ft. to . ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .					
Grout Intervals: From . <u>3</u> ft. to <u>23</u> ft., From . ft. to . ft., From . ft. to . ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well		3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)	
Direction from well? <u>North</u>		How many feet? <u>12</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	12	clay			
12	21	med. sand			
21	22	clay			
22	59	med sand			
59	61	clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-29-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>7-30-92</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Susan K. Weninger</u>					