

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SE 1/4 Section Number 6 Township Number T 27 S Range Number R 1 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?
4 1/2 mi. W. Maize, KS.

2 WATER WELL OWNER: John Kelley
 RR#, St. Address, Box #: 11120 W. 121st North
 City, State, ZIP Code: Wichita, KS 67209
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	
			E
	SW	SE	

4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 5-26-83
 Depth(s) Groundwater Encountered 1. 26 ft. 2. 27 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 5-26-83
 Pump test data: Well water was 27 ft. after 20 hours pumping 20 gpm
 Est. Yield 3000 gpm: Well water was 27 ft. after 20 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 50 ft., and 50 in. to 50 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped X Welded X Threaded X
 Blank casing diameter 5 in. to 12-34 ft., Dia. 1.59 in. to 50 ft., Dia. 50 in. to 50 ft.
 Casing height above land surface 12-34 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 50R-26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 34 ft. to 50 ft. From 34 ft. to 50 ft. From 34 ft. to 50 ft. From 34 ft. to 50 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 50 ft. From 13 ft. to 50 ft. From 13 ft. to 50 ft. From 13 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 50 ft. From 13 ft. to 50 ft. From 13 ft. to 50 ft.
 What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? North
 How many feet? 140

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	23	red clay			
23	32	fine sand			
32	33	clay			
33	50	med gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-26-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-5-83 under the business name of Wenger & Kelley by (signature) [Signature]
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

27

R

E

SEC.

6

SW 1/4

SW 1/4

SW 1/4

SE 1/4

1/4