

1 LOCATION OF WATER WELL: County: Sedg. Fraction: NE 1/4 SE 1/4 NW 1/4 Section Number: 8 Township Number: T 27 S Range Number: R 1 E/W

Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: GEROLD DARGEL
RR#, St. Address, Box #: 9726 W. 18th St Ct.
City, State, ZIP Code: WICHITA KS 67212 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	
S	SW	SE	E

4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 425.94
Depth(s) Groundwater Encountered 1. 23 ft. 2. 23 ft. 3. 23 ft.
WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 4-25-94
Pump test data: Well water was 23 ft. after 20 hours pumping 20 gpm
Est. Yield 50 gpm: Well water was 23 ft. after 20 hours pumping 20 gpm
Bore Hole Diameter 11 in. to 50 ft., and 50 in. to 50 ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
Blank casing diameter 5 in. to 40 ft., Dia. 2.60 in. to 160 ft., Dia. 160 ft., Dia. 160 ft.
Casing height above land surface 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160 ft.
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft., From 40 ft. to 50 ft., From 40 ft. to 50 ft., From 40 ft. to 50 ft.
GRAVEL PACK INTERVALS: From 23 ft. to 50 ft., From 23 ft. to 50 ft., From 23 ft. to 50 ft., From 23 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 23 ft., From 23 ft. to 50 ft., From 50 ft. to 50 ft., From 50 ft. to 50 ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? North How many feet? 16

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	19	clay			
19	32	fine sand			
32	33	clay			
33	50	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-25-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-15-94 under the business name of Wenger's Ditch by (signature) [Signature]