

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW 1/4	SW 1/4	SW 1/4	8	T 27	S	R 1	E/W
Distance and direction from nearest town or city street address of well if located within city?						52895004			
183' NE of the intersection of 13th Street & Malze Rd, Wichita, KS						Amoco No. 2126		MW-3	
2 WATER WELL OWNER: Groundwater Management Section, Amoco Oil Company									
RR#, St. Address, Box # : 7201 E. 38th Street, Space 7253						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Tulsa, OK 74145						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION: Approx. Surface Elev: 1347							
		Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL .27.0 ft. below land surface measured on mo/day/yr 03/08/89							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 9 in. to 34 ft., and in. to ft.							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped							
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)		Welded	
2 PVC		4 ABS		7 Fiberglass				Threaded X	
Blank casing diameter .2 in. to 18 ft., Dia . in. to ft., Dia . in. to ft.									
Casing height above land surface .1 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		11 Other (specify)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 18 ft. to 33 ft., From ft. to ft.							
		From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS:		From 15.5 ft. to 34 ft., From ft. to ft.							
		From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 13.5 ft., From 13.5 ft. to 15.5 ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage			
Direction from well? SE						How many feet? 10			
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS			
0 9		Red-Brown Lean Clay							
9 12		Red-Brown Lean to Fat Sandy Clay							
12 15.5		Red-Brown Clayey Sand							
15.5 19		Red-Brown Medium Sand							
19 34		Brown Medium Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/02/89 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 416						This Water Well Record was completed on (mo/day/yr) 3/28/89			
under the business name of Terracon Consultants, Inc.						by (signature) [Signature]			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									