

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW ¼ SW ¼ SW ¼	Section Number 8	Township Number T 27 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 210' NNE of the Intersection of 13th Street & Maize Rd, Wichita, KS				52895004	Amoco No. 2126 MW-1
2 WATER WELL OWNER: Groundwater Management Section, Amoco Oil Company RR#, St. Address, Box #: 7201 E. 38th Street, Space 7253 Board of Agriculture, Division of Water Resources City, State, ZIP Code : Tulsa, OK 74145 Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 33.5 ft. ELEVATION: Approx. Surface Elev.: 1347 Depth(s) Groundwater Encountered 1... 27 ft. 2... ft. 3... ft. WELL'S STATIC WATER LEVEL ... 26.4 ft. below land surface measured on mo/day/yr 03/08/89 Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield ... N/A gpm: Well water was ... ft. after ... hours pumping ... gpm Bore Hole Diameter ... 9 in. to ... 34 ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter ... 2 in. to ... 18.5 ft., Dia.in. to ...ft., Dia.in. to ...ft. Casing height above land surface ... -2 in., weight ... lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ... 18.5 ft. to ... 33.5 ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From ... 17 ft. to ... 34 ft., From ... ft. to ... ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From ... 0 ft. to ... 15 ft., From ... 15 ft. to ... 17 ft., From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? SE How many feet? 70					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 11.5 Red-Brown Lean Clay 11.5 14.5 Red-Brown Lean Sandy Clay 14.5 25.5 Red-Brown Medium Sand 25.5 34 Red-Brown Medium Sand, Trace Sand and Gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 03/07/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 3/28/89 under the business name of Terracon Consultants, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					