

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 SW 1/4 SW 1/4		Section Number 8	Township Number T 27 S	Range Number R 1	Elev																																				
Distance and direction from nearest town or city street address of well if located within city? 180' N of NE corner of 13th Street and Malze Road; Wichita, KS Amoco #2126 50885093 MW-1																																											
2 WATER WELL OWNER: Groundwater Management Section, Amoco Corporation RR#, St. Address, Box # : 4502 E. 41st Street Board of Agriculture, Division of Water Resources City, State, ZIP Code : Tulsa, OK 74135 Application Number:																																											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 1 Mile		4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: Approx. Surface Elev.: 1346 Depth(s) Groundwater Encountered 1. 25 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 24.8 ft. below land surface measured on mo/day/yr 8/8/88 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X																																									
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 17 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 32 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 17 ft. to 32 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 12.5 ft. to 32 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 8.5 ft. to 12.5 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? South How many feet? 300																																											
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>8</td><td>Brown Silty Lean Clay</td><td></td><td></td><td></td></tr><tr><td>8</td><td>14</td><td>Red-Brown Fine to Medium Sand, Trace Clay</td><td></td><td></td><td></td></tr><tr><td>14</td><td>30</td><td>Yellow-Red-Brown Medium to Coarse Sand</td><td></td><td></td><td></td></tr><tr><td>30</td><td>32</td><td>Gray-Red Coarse Sand</td><td></td><td></td><td></td></tr><tr><td colspan="6">Casing/Screen were removed and well was plugged with cement-bentonite grout to 22 feet on 9/12/88.</td></tr></tbody></table>								FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	8	Brown Silty Lean Clay				8	14	Red-Brown Fine to Medium Sand, Trace Clay				14	30	Yellow-Red-Brown Medium to Coarse Sand				30	32	Gray-Red Coarse Sand				Casing/Screen were removed and well was plugged with cement-bentonite grout to 22 feet on 9/12/88.					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																						
0	8	Brown Silty Lean Clay																																									
8	14	Red-Brown Fine to Medium Sand, Trace Clay																																									
14	30	Yellow-Red-Brown Medium to Coarse Sand																																									
30	32	Gray-Red Coarse Sand																																									
Casing/Screen were removed and well was plugged with cement-bentonite grout to 22 feet on 9/12/88.																																											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/1/88 9/12/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10-10-88 under the business name of Terracon Consultants, Inc by (signature)																																											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.																																											

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4