

1 LOCATION OF WATER WELL County: Sedgwick		Fraction NW 1/4 SE 1/4 SE 1/4	Section Number 8	Township Number T 27 S	Range Number R 1W E/W		
Distance and direction from nearest town or city? in Wichita			Street address of well if located within city? 1604 N Byron				
2 WATER WELL OWNER: Bob Hetherington RR#, St. Address, Box #: 1604 N Byron City, State, ZIP Code: Wichita KS							
Board of Agriculture, Division of Water Resources Application Number:							
3 DEPTH OF COMPLETED WELL: 37 ft. Bore Hole Diameter: 1.1 in. to 27 ft., and 5 in. to 37 ft.							
Well Water to be used as:							
1 Domestic		3 Feedlot		5 Public water supply			
2 Irrigation		4 Industrial		6 Oil field water supply			
		7 Lawn and garden only		8 Air conditioning			
				9 Dewatering			
				11 Injection well			
				12 Other (Specify below)			
				10 Observation well			
Well's static water level: 27 ft. below land surface measured on 9 month 22 day 79 year							
Pump Test Data: Well water was 27 ft. after 1 hours pumping 12 gpm							
Est. Yield 50 gpm: Well water was ft. after hours pumping gpm							
4 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron			
2 PVC		4 ABS		6 Asbestos-Cement			
				7 Fiberglass			
				9 Other (specify below)			
				Casing Joints: Glued X Clamped			
				Welded			
				Threaded			
Blank casing dia. 5.563 in. to 37 ft., Dia. in. to ft., Dia. in. to ft.							
Casing height above land surface: 12 in., weight 2.758 lbs./ft. Wall thickness or gauge No. 258							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass			
2 Brass		4 Galvanized steel		6 Concrete tile			
				9 ABS			
				10 Asbestos-cement			
				11 Other (specify)			
				12 None used (open hole)			
Screen or Perforation Openings Are:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped			
2 Louvered shutter		4 Key punched		6 Wire wrapped			
				7 Torch cut			
				9 Drilled holes			
				10 Other (specify)			
Screen-Perforation Dia. 0.25 in. to ft., Dia. in. to ft., Dia. in. to ft.							
Screen-Perforated Intervals: From 32 ft. to 37 ft., From ft. to ft., From ft. to ft.							
Gravel Pack Intervals: From 27 ft. to 37 ft., From ft. to ft., From ft. to ft.							
5 GROUT MATERIAL:							
1 Neat cement		2 Cement grout		3 Bentonite			
4 Other							
Grouted Intervals: From 8 ft. to 10 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Cess pool		7 Sewage lagoon			
2 Sewer lines		5 Seepage pit		8 Feed yard			
3 Lateral lines		6 Pit privy		9 Livestock pens			
				10 Fuel storage			
				11 Fertilizer storage			
				12 Insecticide storage			
				13 Watertight sewer lines			
				14 Abandoned water well			
				15 Oil well/Gas well			
				16 Other (specify below)			
Direction from well: How many feet 15 ? Water Well Disinfected? Yes X No							
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, date sample							
was submitted month day year: Pump Installed? Yes X No							
If Yes: Pump Manufacturer's name Sta-rite Model No. 83P44002E HP 3/4 Volts 220							
Depth of Pump Intake 34 ft. Pumps Capacity rated at 20 gal./min.							
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other							
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on October month 9 day 1979 year							
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 1829							
This Water Well Record was completed on November month 5 day 1979 year under the business name of List Electric Co. by (signature) John R. Harris							
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		0	27	clay sand, gravel (med)			
		27	37				
ELEVATION:							
Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)							

OFFICE USE ONLY

T

27

R

1

END

SEC.

8

NW 1/4 SE 1/4 SE 1/4