

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction: NE 1/4 SW 1/4 SW 1/4	Section Number: 8	Township Number: T 27 S	Range Number: R 1 E
Distance and direction from nearest town or city street address of well if located within city? 10314 ALAMO CT. WICHITA KANS					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		BOB HANSON 10314 ALAMO CT. WICHITA KANS Board of Agriculture, Division of Water Resources Application Number: NONE			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 1300 FT.			
		Depth(s) Groundwater Encountered 1. 28 ft. 2. 28 ft. 3. 28 ft. WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 5/10/85 Pump test data: Well water was NA ft. after NA hours pumping NA gpm Est. Yield 65 gpm: Well water was NA ft. after NA hours pumping NA gpm Bore Hole Diameter 9 in. to 12 in. and 6 in. to 50 in. ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes NO ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes NO			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 5 in. to 12 1/4 in. Dia. 1.59 in. to 1.59 in. Dia. 1.59 in. to 1.59 in. Dia. 1.59 in. to 1.59 in. Dia. Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SOR 26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft. From 40 ft. to 50 ft. From 40 ft. to 50 ft. From 40 ft. to 50 ft. GRAVEL PACK INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft.			
		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From -2 ft. to 12 ft. From 12 ft. to 12 ft. From 12 ft. to 12 ft. From 12 ft. to 12 ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SO How many feet? 40			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 3 TOP SOIL - DARK BR.					
3 8 CLAY - RED					
8 20 RED SANDY CLAY					
20 28 SAND RED-MED					
28 39 SAND TAN MED					
39 50 SAND TAN COARSE					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/10/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 5/10/85 under the business name of BEARDEN Pump & Well by (signature) Chas W Bearden					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4