

1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 SW 1/4 Section Number 8 Township Number T 27 S Range Number R 1 E
 County: Sedgewick
 Distance and direction from nearest town or city street address of well if located within city?
1521 Amarado Ct. Wichita KS.

2 WATER WELL OWNER: JAY RUSSELL CONST
 RR#, St. Address, Box #: 10300 91st mo. Wichita KS 67212
 City, State, ZIP Code: Wichita KS 67212
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	E
	SW	SE	
S			

4 DEPTH OF COMPLETED WELL: 52 ft. ELEVATION: 3-15-83
 Depth(s) Groundwater Encountered 1. 29 ft. 2. 29 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 29 ft. below land surface measured on mo/day/yr 3-15-83
 Pump test data: Well water was 29 ft. after 2 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 29 ft. after 2 hours pumping 20 gpm
 Bore Hole Diameter 1 1/2 in. to 52 ft., and 52 ft. to 52 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 42 ft., Dia 42 in. to 52 ft., Dia 52 in. to 52 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SOR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 8 RMP (SR)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 8 RMP (SR)
 SCREEN-PERFORATED INTERVALS: From 42 ft. to 52 ft., From 52 ft. to 52 ft., From 52 ft. to 52 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 52 ft., From 52 ft. to 52 ft., From 52 ft. to 52 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 2 Cement grout
 Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 52 ft., From 52 ft. to 52 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Water tight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	21	Red clay			
21	31	fine sand			
31	32	Red clay			
32	52	med gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-15-83 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 4-1-83
 under the business name of Weninger Drilling by (signature) Don Weninger
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

SW

NE

SW

NE

SW

NE

SW

NE

SW

NE

SW

NE

SW

NE

SW

NE

SW

NE

SW

NE